



MyID
Version 10.8 Update 2

Lifecycle API

Lutterworth Hall, St Mary's Road, Lutterworth, Leicestershire, LE17 4PS, UK
www.intercede.com | info@intercede.com | [@intercedemyid](https://twitter.com/intercedemyid) | +44 (0)1455 558111

Copyright

© 2001-2018 Intercede Limited. All rights reserved.

Information in this document is subject to change without notice. The software described in this document is furnished exclusively under a restricted license or non-disclosure agreement. Copies of software supplied by Intercede Limited may not be used resold or disclosed to third parties or used for any commercial purpose without written authorization from Intercede Limited and will perpetually remain the property of Intercede Limited. They may not be transferred to any computer without both a service contract for the use of the software on that computer being in existence and written authorization from Intercede Limited.

The software or web site referred to in this manual may utilize or contain material that is © 1994-2000 DUNDAS SOFTWARE LTD., all rights reserved.

No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or any means electronic or mechanical, including photocopying and recording for any purpose other than the purchaser's personal use without the written permission of Intercede Limited.

Whilst Intercede Limited has made every effort in the preparation of this manual to ensure the accuracy of the information, the information contained in this manual is delivered without warranty, either express or implied. Intercede Limited will not be held liable for any damages caused, or alleged to be caused, either directly or indirectly by this manual.

Licenses and Trademarks

The Intercede® and MyID® word marks and the MyID® logo are registered trademarks of Intercede in the UK, US and other countries.

Microsoft and Windows are registered trademarks of Microsoft Corporation. Other brands and their products are trademarks or registered trademarks of their respective holders and should be noted as such. All other trademarks acknowledged.

Conventions Used in this Document

- Lists:
 - ◆ Numbered lists are used to show the steps involved in completing a task when the order is important
 - ◆ Bulleted lists are used when the order is unimportant or to show alternatives
- **Bold** is used for menu items and for labels.
For example:
 - ◆ “Record a valid email address in ‘From’ email address”
 - ◆ Select **Save** from the **File** menu
- *Italic* is used for emphasis and to indicate references to other sections within the current document.
For example:
 - ◆ “Copy the file *before* starting the installation”
 - ◆ “See *Issuing a Card* for further information”
- **Bold and italic** are used to identify the titles of other documents.
For example: “See the **Release Notes** for further information.”
Unless otherwise explicitly stated, all referenced documentation is available on the product CD.
- A `fixed width font` is used where the identification of spaces is important, including filenames, example SQL queries and any entries made directly into configuration files or the database.
- **Notes** are used to provide further information, including any prerequisites or configuration additional to the standard specifications.
For example:

Note: This issue only occurs if updating from a previous version.
- Warnings are used to indicate where failure to follow a particular instruction may result in either loss of data or the need to manually configure elements of the system.
For example:

Warning: You must take a backup of your database before making any changes to it.

Contents

1	Introduction.....	9
1.1	Change history.....	9
1.2	The Lifecycle API in the card issuance process.....	10
2	Lifecycle API Web Service.....	12
2.1	Installing the service	12
2.2	Security settings	12
2.3	Overview.....	13
2.4	Increasing the maximum pool size.....	13
2.5	Timeouts.....	14
2.6	Known issues.....	14
3	Preparing the data for import.....	15
3.1	CMS and PIV differences.....	15
3.2	Escaping characters	15
3.2.1	DNs.....	15
3.3	Encoding images	16
3.4	Advanced settings	16
3.5	Adding and modifying users.....	17
3.6	Requesting cards.....	17
3.7	Enabling, disabling and removing users	17
3.7.1	Removing users	17
3.7.2	Disabling users	17
3.7.3	Enabling users	17
3.7.4	Status mapping codes	18
3.8	Importing additional fields	23
3.8.1	Additional user fields.....	23
3.8.2	Additional group fields	23
3.8.3	Additional job fields	23
3.9	Importing users into Entrust	23
3.10	Canceling credentials and jobs	24
3.10.1	Canceling cards	24
3.10.2	Canceling jobs	25
3.10.3	Filtering job cancellations.....	25
4	Calling the import service.....	28
4.1	Results.....	28
5	Advanced settings.....	29
5.1	Custom schema and transform files	31
6	Troubleshooting	33
6.1	ASP.NET temporary folder permissions	33
6.2	HTTP Error 500.24 – Internal Server Error	33
7	Data Structure	34
7.1	CMSCardRequest structure	35
7.1.1	CMSCardRequest/Parameters	35
7.1.2	CMSCardRequest/Group.....	35
7.1.3	CMSCardRequest/Group/Name	35
7.1.4	CMSCardRequest/Group/Description.....	35
7.1.5	CMSCardRequest/Group/OrgUnit	35
7.1.6	CMSCardRequest/Group/Parent	35
7.1.7	CMSCardRequest/Group/AdditionalFields.....	36
7.1.8	CMSCardRequest/Group/User	36
7.1.9	CMSCardRequest/Group/User/Personal	36
7.1.10	CMSCardRequest/Group/User/Personal/FirstName.....	36
7.1.11	CMSCardRequest/Group/User/Personal/LastName	36

7.1.12	CMSCardRequest/Group/User/Personal/Initial	37
7.1.13	CMSCardRequest/Group/User/Personal>Title	37
7.1.14	CMSCardRequest/Group/User/Personal>Email	37
7.1.15	CMSCardRequest/Group/User/Personal/PhoneExt.....	37
7.1.16	CMSCardRequest/Group/User/Personal/MobileNumber	37
7.1.17	CMSCardRequest/Group/User/Personal/PhoneNumber	37
7.1.18	CMSCardRequest/Group/User/Personal/EmployeeID	38
7.1.19	CMSCardRequest/Group/User/Personal/OptionalLine1	38
7.1.20	CMSCardRequest/Group/User/Personal/OptionalLine2	38
7.1.21	CMSCardRequest/Group/User/Personal/OptionalLine3	38
7.1.22	CMSCardRequest/Group/User/Personal/OptionalLine4	38
7.1.23	CMSCardRequest/Group/User/Authentication	38
7.1.24	CMSCardRequest/Group/User/Authentication/SecurityPhrase	39
7.1.25	CMSCardRequest/Group/User/Authentication/SecurityPhrase/Prompt	39
7.1.26	CMSCardRequest/Group/User/Authentication/SecurityPhrase/Answer	40
7.1.27	CMSCardRequest/Group/User/Card	41
7.1.28	CMSCardRequest/Group/User/Card/CardProfile	41
7.1.29	CMSCardRequest/Group/User/Card/CardExpiryDate	41
7.1.30	CMSCardRequest/Group/User/Card/Renewal	42
7.1.31	CMSCardRequest/Group/User/Card/CardRequestedBy	42
7.1.32	CMSCardRequest/Group/User/Card/CancelExisting	42
7.1.33	CMSCardRequest/Group/User/Card/JobLabel	42
7.1.34	CMSCardRequest/Group/User/Card/Update	42
7.1.35	CMSCardRequest/Group/User/Card/Update/OriginalSerialNumber	42
7.1.36	CMSCardRequest/Group/User/Card/Update/OriginalDeviceType	43
7.1.37	CMSCardRequest/Group/User/Card/Update/StatusMapping	43
7.1.38	CMSCardRequest/Group/User/Card/Replacement	43
7.1.39	CMSCardRequest/Group/User/Card/Replacement/OriginalSerialNumber	43
7.1.40	CMSCardRequest/Group/User/Card/Replacement/OriginalDeviceType	43
7.1.41	CMSCardRequest/Group/User/Card/Replacement/StatusMapping	43
7.1.42	CMSCardRequest/Group/User/Card/GenerateOTP	44
7.1.43	CMSCardRequest/Group/User/Card/GenerateOTP/Notification	44
7.1.44	CMSCardRequest/Group/User/Card/GenerateOTP/Notification/Name	44
7.1.45	CMSCardRequest/Group/User/Card/GenerateOTP/Notification/Action	44
7.1.46	CMSCardRequest/Group/User/Card/OriginalSerialNumber	45
7.1.47	CMSCardRequest/Group/User/Card/OriginalDeviceType	45
7.1.48	CMSCardRequest/Group/User/Card/SerialNumber	45
7.1.49	CMSCardRequest/Group/User/Card/DeviceType	45
7.1.50	CMSCardRequest/Group/User/Card/StatusMapping	45
7.1.51	CMSCardRequest/Group/User/Card/Reprovision	45
7.1.52	CMSCardRequest/Group/User/Card/CardLayout	46
7.1.53	CMSCardRequest/Group/User/Card/AdditionalFields	46
7.1.54	CMSCardRequest/Group/User/CardUpdate	46
7.1.55	CMSCardRequest/Group/User/CardUpdate/SerialNumber	46
7.1.56	CMSCardRequest/Group/User/CardUpdate/DeviceType	46
7.1.57	CMSCardRequest/Group/User/CardUpdate/CardRequestedBy	46
7.1.58	CMSCardRequest/Group/User/CardUpdate/ParametersXML	46
7.1.59	CMSCardRequest/Group/User/CardUpdate/ParametersXML/UnlockPIN	47
7.1.60	CMSCardRequest/Group/User/CardUpdate/PIN	47
7.1.61	CMSCardRequest/Group/User/Account	47
7.1.62	CMSCardRequest/Group/User/Account/DN	47
7.1.63	CMSCardRequest/Group/User/Account/CN	47
7.1.64	CMSCardRequest/Group/User/Account/OU	47
7.1.65	CMSCardRequest/Group/User/Account/UPN	47
7.1.66	CMSCardRequest/Group/User/Account/SAMAccountName	47
7.1.67	CMSCardRequest/Group/User/Account/LogonName	48
7.1.68	CMSCardRequest/Group/User/Account/NewLogonName	48
7.1.69	CMSCardRequest/Group/User/Account/UniqueId	48
7.1.70	CMSCardRequest/Group/User/Account/Roles	48
7.1.71	CMSCardRequest/Group/User/Account/Roles/Role	48
7.1.72	CMSCardRequest/Group/User/Account/Roles/Role/Name	48
7.1.73	CMSCardRequest/Group/User/Account/Roles/Role/Scope	49
7.1.74	CMSCardRequest/Group/User/Account/Roles/Role/LogonMechanism	49
7.1.75	CMSCardRequest/Group/User/Account/EntrustProfile	49
7.1.76	CMSCardRequest/Group/User/Account/UserDataApproved	49
7.1.77	CMSCardRequest/Group/User/Photo	50
7.1.78	CMSCardRequest/Group/User/Photo/Encoding	50

7.1.79	CMSCardRequest/Group/User/Photo/Data	50
7.1.80	CMSCardRequest/Group/User/Photo/DateTaken	50
7.1.81	CMSCardRequest/Group/User/Photo/Source.....	50
7.1.82	CMSCardRequest/Group/User/Photo/None	51
7.1.83	CMSCardRequest/Group/User/AdditionalFields	51
7.1.84	CMSCardRequest/Group/User/Actions	51
7.1.85	CMSCardRequest/Group/User/Actions/ApplicantAction	51
7.1.86	CMSCardRequest/Group/User/Actions/CertSerialNumber	52
7.1.87	CMSCardRequest/Group/User/Actions/CertPolicyName.....	52
7.1.88	CMSCardRequest/Group/User/Actions/StatusMappingID	52
7.1.89	CMSCardRequest/Group/User/Actions/RevocationComment	52
7.1.90	CMSCardRequest/Group/User/Actions/RevocationDelay	52
7.1.91	CMSCardRequest/Group/User/Actions/Device.....	52
7.1.92	CMSCardRequest/Group/User/Actions/Device/DeviceIdentifier	52
7.1.93	CMSCardRequest/Group/User/Actions/Device/DeviceIdentifier/SerialNumber	52
7.1.94	CMSCardRequest/Group/User/Actions/Device/DeviceIdentifier/SerialNumberField	53
7.1.95	CMSCardRequest/Group/User/Actions/Device/ProcessStatus.....	53
7.1.96	CMSCardRequest/Group/User/Actions/RequestedBy	53
7.1.97	CMSCardRequest/Group/User/Actions/Job.....	54
7.1.98	CMSCardRequest/Group/User/Actions/Filters.....	54
7.2	CMSUserUpdate structure.....	55
7.3	CMSImportReponse structure	56
7.3.1	CMSImportResponse/Group.....	56
7.3.2	CMSImportResponse/Group/Name	56
7.3.3	CMSImportResponse/Group/Result	56
7.3.4	CMSImportResponse/Group/User	56
7.3.5	CMSImportResponse/Group/User/FirstName.....	56
7.3.6	CMSImportResponse/Group/User/LastName.....	57
7.3.7	CMSImportResponse/Group/User/EmployeeID.....	57
7.3.8	CMSImportResponse/Group/User/LogonName.....	57
7.3.9	CMSImportResponse/Group/User/CardRequest	57
7.3.10	CMSImportResponse/Group/User/UnlockCardRequest	57
7.3.11	CMSImportResponse/Group/User/Result	57
7.3.12	CMSImportResponse/Group/User/error.....	58
7.4	PivCardRequest.....	59
7.4.1	PivCardRequest/Parameters	60
7.4.2	PivCardRequest/Agency	60
7.4.3	PivCardRequest/Agency/DeptCode	60
7.4.4	PivCardRequest/Agency/AgencyCode	60
7.4.5	PivCardRequest/Agency/FacilityCode	60
7.4.6	PivCardRequest/Agency/AgencyName	60
7.4.7	PivCardRequest/Agency/FacilityName	61
7.4.8	PivCardRequest/Agency/DUNS.....	61
7.4.9	PivCardRequest/Agency/OC	61
7.4.10	PivCardRequest/Agency/OI	61
7.4.11	PivCardRequest/Agency/Department	61
7.4.12	PivCardRequest/Agency/BaseDN	62
7.4.13	PivCardRequest/Agency/Parent	62
7.4.14	PivCardRequest/Agency/AgencyAddress	62
7.4.15	PivCardRequest/Agency/AdditionalAgencyFields.....	62
7.4.16	PivCardRequest/Agency/Applicant	63
7.4.17	PivCardRequest/Agency/Applicant/Personal	63
7.4.18	PivCardRequest/Agency/Applicant/Personal/FirstName	63
7.4.19	PivCardRequest/Agency/Applicant/Personal/LastName	63
7.4.20	PivCardRequest/Agency/Applicant/Personal/NickName	63
7.4.21	PivCardRequest/Agency/Applicant/Personal/MiddleName	63
7.4.22	PivCardRequest/Agency/Applicant/Personal/Suffix	63
7.4.23	PivCardRequest/Agency/Applicant/Personal/Title	63
7.4.24	PivCardRequest/Agency/Applicant/Personal/Email	64
7.4.25	PivCardRequest/Agency/Applicant/Personal/Fax	64
7.4.26	PivCardRequest/Agency/Applicant/Personal/Cell	64
7.4.27	PivCardRequest/Agency/Applicant/Personal/Phone.....	64
7.4.28	PivCardRequest/Agency/Applicant/Personal/EmployeeID	64
7.4.29	PivCardRequest/Agency/Applicant/Personal/Address	64
7.4.30	PivCardRequest/Agency/Applicant/Personal/BirthDate	65
7.4.31	PivCardRequest/Agency/Applicant/Personal/Nationality	65

7.4.32	PivCardRequest/Agency/Applicant/Personal/Citizenship	74
7.4.33	PivCardRequest/Agency/Applicant/Personal/CountryOfBirth	74
7.4.34	PivCardRequest/Agency/Applicant/Personal/PlaceOfBirth	74
7.4.35	PivCardRequest/Agency/Applicant/Personal/ExportRestrictions	74
7.4.36	PivCardRequest/Agency/Applicant/Authentication	74
7.4.37	PivCardRequest/Agency/Applicant/Authentication/SecurityPhrase	75
7.4.38	PivCardRequest/Agency/Applicant/Authentication/SecurityPhrase/Prompt	75
7.4.39	PivCardRequest/Agency/Applicant/Authentication/SecurityPhrase/Answer	76
7.4.40	PivCardRequest/Agency/Applicant/Card	77
7.4.41	PivCardRequest/Agency/Applicant/Card/CardProfile	77
7.4.42	PivCardRequest/Agency/Applicant/Card/CardExpiryDate	77
7.4.43	PivCardRequest/Agency/Applicant/Card/Renewal	78
7.4.44	PivCardRequest/Agency/Applicant/Card/CardRequestedBy	78
7.4.45	PivCardRequest/Agency/Applicant/Card/JobLabel	78
7.4.46	PivCardRequest/Agency/Applicant/Card/Update	78
7.4.47	PivCardRequest/Agency/Applicant/Card/Update/OriginalSerialNumber	78
7.4.48	PivCardRequest/Agency/Applicant/Card/Update/OriginalDeviceType	78
7.4.49	PivCardRequest/Agency/Applicant/Card/Update/StatusMapping	78
7.4.50	PivCardRequest/Agency/Applicant/Card/Replacement	79
7.4.51	PivCardRequest/Agency/Applicant/Card/Replacement/OriginalSerialNumber	79
7.4.52	PivCardRequest/Agency/Applicant/Card/Replacement/OriginalDeviceType	79
7.4.53	PivCardRequest/Agency/Applicant/Card/Replacement/StatusMapping	79
7.4.54	PivCardRequest/Agency/Applicant/Card/Reprovision	79
7.4.55	PivCardRequest/Agency/Applicant/Card/CardLayout	79
7.4.56	PivCardRequest/Agency/Applicant/Card/SerialNumber	80
7.4.57	PivCardRequest/Agency/Applicant/Card/DeviceType	80
7.4.58	PivCardRequest/Agency/Applicant/Account	80
7.4.59	PivCardRequest/Agency/Applicant/Account/DN	80
7.4.60	PivCardRequest/Agency/Applicant/Account/AlternateDN	80
7.4.61	PivCardRequest/Agency/Applicant/Account/CN	80
7.4.62	PivCardRequest/Agency/Applicant/Account/OU	80
7.4.63	PivCardRequest/Agency/Applicant/Account/UPN	80
7.4.64	PivCardRequest/Agency/Applicant/Account/SAMAccountName	81
7.4.65	PivCardRequest/Agency/Applicant/Account/Domain	81
7.4.66	PivCardRequest/Agency/Applicant/Account/LogonName	81
7.4.67	PivCardRequest/Agency/Applicant/Account/Roles	81
7.4.68	PivCardRequest/Agency/Applicant/Account/Roles/Role	81
7.4.69	PivCardRequest/Agency/Applicant/Account/EntrustProfile	82
7.4.70	PivCardRequest/Agency/Applicant/Position	82
7.4.71	PivCardRequest/Agency/Applicant/Position/EmployeeAssociation	82
7.4.72	PivCardRequest/Agency/Applicant/Position/EmployeeAffiliation	83
7.4.73	PivCardRequest/Agency/Applicant/Position/Rank	83
7.4.74	PivCardRequest/Agency/Applicant/Position/EmergencyRole	83
7.4.75	PivCardRequest/Agency/Applicant/Position/Privilege	83
7.4.76	PivCardRequest/Agency/Applicant/Position/ApplicantPosition	84
7.4.77	PivCardRequest/Agency/Applicant/Position/ExtraInfo	84
7.4.78	PivCardRequest/Agency/Applicant/Sponsor	84
7.4.79	PivCardRequest/Agency/Applicant/Sponsor/SponsorName	84
7.4.80	PivCardRequest/Agency/Applicant/Sponsor/SponsorPosition	84
7.4.81	PivCardRequest/Agency/Applicant/Sponsor/SponsorAgency	84
7.4.82	PivCardRequest/Agency/Applicant/Sponsor/SponsorEmail	84
7.4.83	PivCardRequest/Agency/Applicant/Sponsor/SponsorPhoneNumber	84
7.4.84	PivCardRequest/Agency/Applicant/Biometry	85
7.4.85	PivCardRequest/Agency/Applicant/Biometry/HeightInches	85
7.4.86	PivCardRequest/Agency/Applicant/Biometry/WeightLbs	85
7.4.87	PivCardRequest/Agency/Applicant/Biometry/Gender	85
7.4.88	PivCardRequest/Agency/Applicant/Biometry/EyeColor	85
7.4.89	PivCardRequest/Agency/Applicant/Biometry/HairColor	86
7.4.90	PivCardRequest/Agency/Applicant/Biometry/Race	86
7.4.91	PivCardRequest/Agency/Applicant/Biometry/BioSample	87
7.4.92	PivCardRequest/Agency/Applicant/Biometry/Signature	89
7.4.93	PivCardRequest/Agency/Applicant/IdentityDocs	89
7.4.94	PivCardRequest/Agency/Applicant/NACI	91
7.4.95	PivCardRequest/Agency/Applicant/NACI/NACCCaseNumber	91
7.4.96	PivCardRequest/Agency/Applicant/NACI/NACICaseNumber	91
7.4.97	PivCardRequest/Agency/Applicant/NACI/Check	92
7.4.98	PivCardRequest/Agency/Applicant/NACI/CardIssuanceApproved	92

7.4.99	PivCardRequest/Agency/Applicant/NACI/Comments	93
7.4.100	PivCardRequest/Agency/Applicant/Photo	93
7.4.101	PivCardRequest/Agency/Applicant/System	93
7.4.102	PivCardRequest/Agency/Applicant/System/GUID	93
7.4.103	PivCardRequest/Agency/Applicant/System/CredNo	93
7.4.104	PivCardRequest/Agency/Applicant/System/CS	93
7.4.105	PivCardRequest/Agency/Applicant/System/POA	94
7.4.106	PivCardRequest/Agency/Applicant/System/ICI	94
7.4.107	PivCardRequest/Agency/Applicant/System/UserStatus	94
7.4.108	PivCardRequest/Agency/Applicant/System/IssuanceNotifyURL	95
7.4.109	PivCardRequest/Agency/Applicant/System/CancelNotifyURL	95
7.4.110	PivCardRequest/Agency/Applicant/System/CMSIssuanceNotifyURL	95
7.4.111	PivCardRequest/Agency/Applicant/AdditionalFields	95
7.4.112	PivCardRequest/Agency/Applicant/Actions	95
7.4.113	PivCardRequest/Agency/Applicant/Actions/ApplicantAction	95
7.4.114	PivCardRequest/Agency/Applicant/Actions/CertSerialNumber	96
7.4.115	PivCardRequest/Agency/Applicant/Actions/CertPolicyName	96
7.4.116	PivCardRequest/Agency/Applicant/Actions/StatusMappingID	96
7.4.117	PivCardRequest/Agency/Applicant/Actions/RevocationComment	96
7.4.118	PivCardRequest/Agency/Applicant/Actions/Device	96
7.4.119	PivCardRequest/Agency/Applicant/Actions/Device/DeviceIdentifier	96
7.4.120	PivCardRequest/Agency/Applicant/Actions/Device/DeviceIdentifier/SerialNumber	97
7.4.121	PivCardRequest/Agency/Applicant/Actions/Device/DeviceIdentifier/SerialNumberField	97
7.4.122	PivCardRequest/Agency/Applicant/Actions/Device/ProcessStatus	97
7.4.123	PivCardRequest/Agency/Applicant/Actions/Job	98
7.5	PivApplicantUpdate structure	98
7.6	PivImportResponse structure	98
7.6.1	PivImportResponse/Agency	98
7.6.2	PivImportResponse/Agency/AgencyName	98
7.6.3	PivImportResponse/Agency/AgencyCode	99
7.6.4	PivImportResponse/Agency/Result	99
7.6.5	PivImportResponse/Agency/Applicant	99
7.6.6	PivImportResponse/Agency/Applicant/FirstName	99
7.6.7	PivImportResponse/Agency/Applicant/LastName	99
7.6.8	PivImportResponse/Agency/Applicant/EmployeeID	99
7.6.9	PivImportResponse/Agency/Applicant/CardRequest	100
7.6.10	PivImportResponse/Agency/Applicant/CardRequestFailReason	100
7.6.11	PivImportResponse/Agency/Applicant/Result	100
8	MyIDEnroll WSDL	101
9	XML schemas	105
9.1	Schema file locations	105
9.2	MyIDBaseTypes	106
9.3	CMSSchemaTypes	109
9.4	CMSCardRequest schema	115
9.5	CMSUserUpdate schema	118
9.6	CMSImportResponse schema	119
9.7	PIVSchemaTypes	121
9.8	PivCardRequest	136
9.9	PivApplicantUpdate	139
9.10	PivImportResponse	141

1 Introduction

The MyID® Lifecycle API allows you to add and update users in the MyID database by sending XML documents to a web service. You can also request credentials that can then be collected from any MyID card issuing station.


Note: You cannot use the Lifecycle API to request mobile credentials; instead, you must use the Credential Web Service. See the [Credential Web Service](#) document for details.

1.1 Change history

Version	Description
IMP1751-01	First version for MyID 10.0.
IMP1751-02	The <code>CreateUnknownGroups</code> parameter is deprecated.
IMP1751-03	New split schema structure. Updated job filtering capabilities. New node for job labels. New nodes for card replacements. New nodes for card updates. New node for SAM Account Name. New nodes for additional photo information. Differences between CMSUserUpdate and CMSCardRequest schema listed. New node for card updates in the import response XML. New node for errors in the import response XML. PIV schemas added.
IMP1751-04	Update for MyID 10.2.
IMP1751-05	Update for MyID 10.3. Removed mention of eDB Data Import Server. Added <code>DisallowCertificateSuspension</code> and <code>CardRequestThrottling</code> parameters. New <code>CardRequestFailReason</code> node. Removing photos from user accounts. <code>DefaultUserRole</code> now available in CMS parameters.
IMP1751-06	Update for MyID 10.4. Clarification for group name uniqueness. Clarification for logon name requirements.
IMP1751-07	Update for MyID 10.5.
IMP1751-08	Update for MyID 10.6.
IMP1751-09	Update for MyID 10.6 Update 1.
IMP1751-10	Update for MyID 10.7.
IMP1751-11	Specify a <code>Domain</code> when importing a PIV user.
IMP1751-12	Update for MyID 10.7 Update 1. Security settings updated.

Version	Description
IMP1751-13	Update for MyID 10.8. New CardLayout node. SerialNumber and DeviceType nodes for targeted issuance now available for PIV as well as CMS. Parameters for PIV and CMS schemas updated to be the same. New ReplaceUnassignedCards parameter.
IMP1751-14	Correction to listings of CMSCardRequest and PivCardRequest schemas. Custom schema support.
IMP1751-15	Update for MyID 10.8 Update 2. Updated list of hair colors.

1.2 The Lifecycle API in the card issuance process




1. External to MyID, capture the user data, including the user's picture.
2. Compile the data into an XML document. Encode the image into this file.
3. Send the XML data to the MyIDEnroll web service.

-
- 4. MyID imports the user data, then passes back an XML report containing information on whether the user's record was imported correctly. MyID creates a card request for the added person.
 - 5. If the credential profile being issued requires validation, the card request must be approved in MyID.
 - 6. When the card is issued, MyID submits requests for certificates to the certificate authority.
 - 7. MyID sends a notification through HTTP to the applicant enroller that the card has been issued.
Contact Intercede professional services for information on setting up notifications.
 - 8. The enroller can then notify other systems that the card has been issued and activated.

2 Lifecycle API Web Service

2.1 Installing the service

You must install the **Lifecycle API Web Services** tier when you install MyID. See the [Installation and Configuration Guide](#) for details.



2.2 Security settings

When the Lifecycle API web service (MyIDEnroll) is installed, it is configured so that it is impossible to authenticate to the service (a combination of **ASP.NET Impersonation** and **Windows Authentication** means you cannot call the web service). If you try to call the web service, you will see an error similar to the following:

HTTP Error 500.24 – Internal Server Error

The Lifecycle API is a powerful feature that allows a caller to add users, edit users, and request issuance of credentials; therefore you *must* restrict its usage.

If your system requires the Lifecycle API to be available to trusted callers, you must configure IIS to allow this.


Review the authentication requirements for the MyIDEnroll web service in IIS and configure it. For more information, see the [Securing Websites and Web Services](#) document.

For production systems, you must ensure anonymous access is disabled.

Once you have configured the authentication mechanism you want to use for MyIDEnroll, disable the **ASP.NET Impersonation** option for the web service in IIS; if you are not using **Windows Authentication**, you must also disable this option.

2.3 Overview

The web service communicates with the MyID server components (the BOL) to import the data.



You post the XML document to the web service. This service processes the XML and passes the transformed data to the BOL.

The BOL performs actions on the data, updating the database if necessary, then returns a response to the web service describing the actions it has carried out. The web service then returns the status to the sender.

2.4

Increasing the maximum pool size

When using MyID web services (for example, MyIDEnroll) under heavy load, you may experience some problems; these may be caused by the .Net framework not releasing COM components correctly, affecting the eConfiguration objects used by MyID.

To solve this issue, you can increase the maximum pool size:

1. Open the Windows Component Services MMC snapin.
2. Expand **Component Service > Computers > My Computer > COM+ Applications > Edefice_BOL > Components**.
3. Right-click **EConfiguration.Configuration.1**, then from the pop-up menu select **Properties**.
4. Click the **Activation** tab.
5. Set the **Maximum Pool Size** to **100**.
6. Click **OK**.

Once you have made the change, you must restart the Edefice_BOL component.

7. Open the Windows Component Services MMC snapin.
8. Expand **Component Service > Computers > My Computer > COM+ Applications**.
9. Right-click **Edefice_BOL** and select **Shut down** from the pop-up menu.

The component will start again automatically when it is next needed.

2.5 Timeouts

If the import process takes too long to process, the Lifecycle API returns an error message stating that the process timed out. For example:

```
<PivImportResponse
xmlns="http://www.intercede.com/MyIDPIVSchema/PIVImportResponse">
<error>
<description>System.Runtime.InteropServices.COMException (0x800468CA) :
Error: 0x800468ca : AsyncJob - Timed out waiting for import response
Info: ASyncImport.EXE
-----
Exception raised in function: CFileImportImpl::ProcessFileImport
In file .\FileImportImpl.cpp at line 475

at EDEFICE_BOLLib.EdeficeBOLClass.ProcessFileImport(String bstrXMLInstructions)
at MyIDEnroll.transferData(XmlDocument outputXML)
at MyIDEnroll.PIVXMLWebImport(String xmlIn)</description>
</error>
</PivImportResponse>
```

The timeout is set to 60 seconds by default. If you want to change this value, you can edit the registry on the MyID application server.

In the following area of the registry:

HKEY_LOCAL_MACHINE\SOFTWARE\Intercede\Edefice\ImportExport

Set the `Timeout` DWORD value to the number of seconds the service will wait for an import to complete.

2.6 Known issues

- **IKB-67 – Limit to concurrent transactions**

Performance of this web service may vary based on a range of factors. This includes network load, server performance, and the volume of transactions taking place within the MyID architecture. For example, the API is expected to operate correctly with up to 15 concurrent transactions taking place. However, beyond this level, further issues may occur such as database timeouts. Increasing server performance may help overcome these issues, but the predicted volumes for your business processes should be part of your capacity planning of the solution.

3

Preparing the data for import

You must create an XML document containing all of the data you want to import using the XML web import service.

The XML document may contain information such as:

- Data for a user
- Core user fields
- User security phrases
- User role and scope to use
- Entrust profile to use
- Extended user fields
- Core group fields
- Extended group fields
- Credential profile to use
- Card expiry date
- Card renewal request
- Images: user photographs and document scans

To make sure the data is transformed into the correct format, you must use an XML schema supported by MyID. See section [9, XML schemas](#) for details of the schemas you can use.

Different schemas are available for adding new users to MyID and updating existing users.

3.1

CMS and PIV differences

While the CMS and PIV schemas have similarities, the PIV schema contains extra information to allow you to import information about PIV applicants and PIV agencies, and is appropriate only for PIV-based systems.

In addition, where the user node in CMS schemas is called `<User>`, in PIV the corresponding node is `<Applicant>`. Similarly, in CMS schemas, the group node is called `<Group>`, while in PIV the corresponding node is `<Agency>`.

Note: Do not use the CMS schemas to request or update PIV cards. You can, however, use the CMS schemas to request or update CIV cards.

3.2

Escaping characters

You must use valid XML for your import files; this includes escaping special characters such as `&`, `<` and `>`. If the XML is invalid, the import service will not process it.

3.2.1

DNs

MyID assumes that the DN is correctly escaped; if it is not, any people in that group will have invalid DNs. To correct this, you must remove the person, correct the group base DN, then add the person again.

The characters that you must escape are:

`,` `=` `+` `<` `>` `\` `#` `;` `"`

To use any of these characters, you must enclose them in double quotes. Additionally, you must prefix any " (double quote) or \ (slash) character with a \ (slash).

For example:

John Smith, Jnr

should be escaped as

```
cn="John Smith, Jnr", o=...
```

If you have an o value of:

Smith "Budget" Cars

this should be escaped as:

```
o="Smith \"Budget\" Cars", c=...
```

3.3 Encoding images

You must encode the images with Base64 encoding within the XML document. The XML web import service can then extract the image data and upload the images to the MyID database.

3.4 Advanced settings

Settings are stored in a file called `settings.xml` in the same folder as the `MyIDEnroll.asmx` file.

The following parameters are available:

- SourceID
- IssueDate
- GenerateUserDN
- ActionOnDuplicate
- RolesActionOnDuplicate
- DeleteMissingUsers
- PushToLDAP
- CreateUnknownGroups – **deprecated**
- AuditAll
- DataType
- CheckImportResponseSchema
- SynchronousImport – **deprecated**. Do not use.
- DefaultUserRole
- DisallowCertificateSuspension – PIV systems only.
- CardRequestThrottling – PIV systems only.

You can include these settings in your XML import document; these settings override any default settings from the `settings.xml` file. If the settings are missing from the XML document, the values in the `settings.xml` file are used instead.

See section [5, Advanced settings](#) for details of the parameters available in the XML import document.

3.5 Adding and modifying users

When you provide the XML import information to the import web service, if the user does not already exist, the user is created. If the user already exists, but you provide different details for the user, the user is updated in the MyID database.

3.6 Requesting cards

When you provide the XML information to the import web service, if you provide details of a card in the `<Card>` node, a card request is created.

Note: If the user already exists in the database, you must set the `<Renewal>` node to `true`, or card request jobs will *not* be created.

3.7 Enabling, disabling and removing users

You can use the import feature to enable, disable or remove users. To disable or remove a user, add a keyword to the XML import file.

Note: There is no response returned when you enable, disable or remove a user through the import process.

3.7.1 Removing users

In the user node (User for CMS, Applicant for PIV), add an `<Actions>` node. Within this, add the following to remove the user:

```
<ApplicantAction>Remove</ApplicantAction>
<StatusMappingID>ID</StatusMappingID>
<RevocationComment>Comment</RevocationComment>
```

Where `ID` is the ID of the revocation or suspension code from the `StatusMapping` table in the database (see section [3.7.4, Status mapping codes](#)), and `Comment` specifies the comment used when revoking or suspending user certificates, and also appears in the system audit reports.

3.7.2 Disabling users

To disable a user, use the following:

```
<ApplicantAction>Disable</ApplicantAction>
<StatusMappingID>ID</StatusMappingID>
<RevocationComment>Comment</RevocationComment>
```

Where `ID` is the ID of the revocation or suspension code from the `StatusMapping` table in the database (see section [3.7.4, Status mapping codes](#)), and `Comment` specifies the comment used when revoking or suspending user certificates, and also appears in the system audit reports.

The user is removed or disabled, and their cards and certificates are canceled or suspended as appropriate.

3.7.3 Enabling users

If you omit the `<Actions>` node, and the user is already in the database and disabled, the import process enables the user again.

3.7.4 Status mapping codes

The following table lists the default status mapping codes from the `StatusMapping` table in the MyID database.

Note: These are the default settings, and may be customized for your own installation. When using the Lifecycle API, you cannot specify the mapping codes with negative IDs – these are reserved for system use.

ID	Status	Description
-8	Automated shared certificate update	System use only, do not use.
-7	Update requested by API	System use only, do not use.
-6	Other Device issued	System use only, do not use.
-5	Revoked/Suspend for timeout at deferred collection	System use only, do not use.
-4	Revoked/Suspend due to timeout in issuance	System use only, do not use.
-3	Revoked/Suspended due to user disabled in LDAP	System use only, do not use.
-2	Revoked due to user removal from LDAP	System use only, do not use.
-1	Revoked due to too many suspensions	System use only, do not use.
0	Unspecified or Automated Processes	System use only, do not use.
1	Lost	The device has been permanently lost.
2	Damaged	The device has been rendered inoperable and should be permanently replaced.
3	Stolen	The device has been stolen and should be replaced.
4	Forgotten	The device has been misplaced and a temporary replacement is required.
5	Permanently Blocked	The device should no longer be used.
6	Compromised	The device has been compromised. A replacement is required.
7	Device holder on leave	The device holder is away temporarily and the device should no longer work until it is re-enabled.
8	Pending Investigation	The device is being investigated and should be suspended temporarily. The device should no longer work until it is re-enabled.
9	Non-payment of services	The device should be disabled permanently.
10	Device holder leaving or changing role	The device holder has left their current role and their device should be blocked permanently.
11	Device holder details change	Information about the device holder has been changed and a new device is needed.
12	Pending Activation	The device is temporary suspended pending activation.
15	Revocation (other)	The device has been permanently blocked for a user-defined reason.
16	Suspension (other)	The device has been temporarily suspended for a user-defined reason.

ID	Status	Description
17	Found Original	This temporary device has been revoked because the device holder found their original device.
18	Original device Compromised	The original device has been compromised so this device must also be considered to have been compromised.
19	Request device Renewal	This device is being replaced or refreshed and shall no longer be active on the system; all certificates will be available for the replacement device.
20	Batch Failed	The device was as part of a batch that failed and must be permanently cancelled.
21	Bureau Failure	There was a failure at the bureau and the device must be permanently cancelled.
22	Processing Failure	There was a processing failure and the device must be permanently cancelled.
25	Poor print quality	The device was printed to an unacceptable standard and must be permanently cancelled.
26	Printing misaligned	The printing on the device is not aligned properly and the device must be permanently cancelled.
27	Poor lamination quality	The device was laminated incorrectly and must be permanently cancelled.
28	Incorrect layout printed	The device was printed with the incorrect layout and must be permanently cancelled.
32	Cancel device and leave Certificates	The device is to be cancel but the certificates are to remain active.
33	Cancel Certificates and leave device	The certificates are to be cancelled but the device is to remain active.
66	Derived Credential Notification Listener	Cancels Derived Credentials on notification of the original credential being revoked.
70	Compromised – Reissue Shared Certificates	A device has been compromised; any certificates shared with other devices will be reissued.
71	Credential Profile Update (no revocation)	There has been an update to the credential profile, but no certificates will be revoked.
72	Credential Profile Update (full revocation)	There has been an update to the credential profile and all certificates will be revoked.
73	Details Change – re-issue archived certificates	The user's details have been changed and all certificates must be re-issued. Non-archived certificates will not be revoked.

Status mapping actions for PIV systems

The following table shows the specific actions for certificates and archived certificates for each status mapping code on a PIV system.

ID	PKI Action	Archive PKI Action (PIV)
-8	Do not revoke; allow recovery to new device.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-7	Do not revoke; allow recovery to new device.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-6	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-5	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.

ID	PKI Action	Archive PKI Action (PIV)
-4	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-3	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-2	Revoke.	Revoke.
-1	Revoke.	Revoke.
0	Revoke.	Revoke.
1	Revoke.	Revoke.
2	Revoke.	Revoke.
3	Revoke.	Revoke.
4	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
5	Revoke.	Revoke.
6	Revoke.	Revoke.
7	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
8	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
9	Revoke.	Revoke.
10	Revoke.	Revoke.
11	Revoke.	Revoke.
12	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
15	Revoke.	Revoke.
16	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
17	Revoke.	Do not revoke. Certificate is available for live recovery on subsequent devices.
18	Revoke.	Revoke.
19	Do not revoke; allow recovery to new device.	Do not revoke. Certificate is available for live recovery on subsequent devices.
20	Revoke.	Revoke.
21	Revoke.	Revoke.
22	Do not revoke.	Revoke.
25	Revoke.	Revoke.
26	Revoke.	Revoke.
27	Revoke.	Revoke.
28	Revoke.	Revoke.
32	Do not revoke. Certificate is available for live recovery on subsequent devices.	Do not revoke. Certificate is available for live recovery on subsequent devices.
33	Revoke.	Revoke.
66	Revoke.	Revoke.
70	Revoke.	Revoke.
71	Do not revoke; allow recovery to new device.	Do not revoke. Certificate is available for live recovery on subsequent devices.

ID	PKI Action	Archive PKI Action (PIV)
72	Revoke.	Revoke.
73	Do not revoke.	Revoke.

Status mapping actions for non-PIV systems

The following table shows the specific actions for certificates and archived certificates for each status mapping code on a non-PIV system.

ID	PKI Action	Archive PKI Action (non-PIV)
-8	Do not revoke; allow recovery to new device.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-7	Do not revoke; allow recovery to new device.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-6	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-5	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-4	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-3	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
-2	Revoke.	Revoke.
-1	Revoke.	Revoke.
0	Revoke.	Revoke.
1	Revoke.	Revoke.
2	Revoke.	Do not revoke. Certificate is available for live recovery on subsequent devices.
3	Revoke.	Revoke.
4	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
5	Revoke.	Do not revoke. Certificate is available for live recovery on subsequent devices.
6	Revoke.	Revoke.
7	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
8	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
9	Revoke.	Revoke.
10	Revoke.	Revoke.
11	Revoke.	Revoke.
12	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
15	Revoke.	Revoke.
16	Suspend.	Do not revoke. Certificate is available for live recovery on subsequent devices.
17	Revoke.	Do not revoke. Certificate is available for live recovery on subsequent devices.
18	Revoke.	Revoke.

ID	PKI Action	Archive PKI Action (non-PIV)
19	Do not revoke; allow recovery to new device.	Do not revoke. Certificate is available for live recovery on subsequent devices.
20	Revoke.	Revoke.
21	Revoke.	Revoke.
22	Do not revoke.	Revoke.
25	Revoke.	Revoke.
26	Revoke.	Revoke.
27	Revoke.	Revoke.
28	Revoke.	Revoke.
32	Do not revoke. Certificate is available for live recovery on subsequent devices.	Do not revoke. Certificate is available for live recovery on subsequent devices.
33	Revoke.	Revoke.
66	Revoke.	Revoke.
70	Revoke.	Revoke.
71	Do not revoke; allow recovery to new device.	Do not revoke. Certificate is available for live recovery on subsequent devices.
72	Revoke.	Revoke.
73	Do not revoke.	Revoke.

3.8 Importing additional fields

Note: Attempting to import an additional field that does not exist in the database causes a failure.

3.8.1 Additional user fields

You can import information into additional extended fields using the data import. In the user node, add an `<AdditionalFields>` node. Within this, add a node for each additional user (`xu`) field you want to import for the user.

For example:

```
<AdditionalFields>
  <Xu1000>User Information</Xu1000>
  <Xu1001>More User Information</Xu1001>
  <Xu1002>Even More User Information</Xu1002>
</AdditionalFields>
```

3.8.2 Additional group fields

You can also add additional information to the group. For CMS, within the group node, add an `<AdditionalFields>` node. For PIV, within the agency node, add an `<AdditionalAgencyFields>` node.

Within this, add a node for each additional group (`xg`) field that you want to import into the group's record.

For example:

```
<AdditionalFields>
  <Xg1000>Group Information</Xg1000>
</AdditionalFields>
```

If you add extended user (`xu`) fields to the `AdditionalFields` node in the group node, or extended group (`xg`) fields to the `AdditionalFields` node in the user node, these are ignored.

3.8.3 Additional job fields

To add additional information to the job created, add an `<AdditionalFields>` node to the `<Card>` node. Within this, add a node for each additional job (`xj`) field you want to import.

3.9 Importing users into Entrust

If you add the `<EntrustProfile>` node to the `<Account>` node, you can specify an Entrust profile for the user. If this node is present in the import XML, the user is added to Entrust using the specified Entrust Profile Template.

For example:

```
<Account>
  ...
  <EntrustProfile>MyEntrustTemplate</EntrustProfile>
</Account>
```

3.10 Canceling credentials and jobs

You can cancel credentials (for example, smart cards) and jobs using the `CMSCardRequest` method through the import service.

Note: If you want to cancel credentials or jobs, you do not have to include a `Card` node unless you also want to request a card at the same time.

3.10.1 Canceling cards

To cancel all of a user's credentials, pass an `ApplicantAction` of `CancelDevices`; for example:

```
<Actions>
  <ApplicantAction>CancelDevices</ApplicantAction>
  <StatusMappingID>ID</StatusMappingID>
  <RevocationComment>Comment</RevocationComment>
</Actions>
```

To cancel a specific credential, pass an `ApplicantAction` of `CancelDevice`. To identify the card you must include a `Device` node containing the card's serial number and device type.

You can cancel more than one credential in a single request by including more than one `Device` element.

Because not all systems track the serial number of the card, you can use a lookup mechanism to identify the card. For each field you want to look up, include the following:

```
<DeviceIdentifier>
  <SerialNumber>[identifier]</SerialNumber>
  <SerialNumberField>[field to look up]</SerialNumberField>
</DeviceIdentifier>
```

The field can be the name of any field present in the `vDevices` view; for example, `SerialNumber` for the standard card serial number, or `HIDSerialNumber` for the HID serial number. You can have multiple `DeviceIdentifier` nodes for each device.

For example, to cancel a card with `HIDSerialNumber 0011778`, pass through the following:

```
<Actions>
  <ApplicantAction>CancelDevice</ApplicantAction>
  <StatusMappingID>ID</StatusMappingID>
  <RevocationComment>Comment</RevocationComment>
  <Device>
    <DeviceIdentifier>
      <SerialNumber>0011778</SerialNumber>
      <SerialNumberField>HIDSerialNumber</SerialNumberField>
      <DeviceTypeName>DeviceCorp</DeviceTypeName>
    </DeviceIdentifier>
  </Device>
</Actions>
```

You can cancel only the cards associated with the applicant. You can cancel suspended cards. You must pass the fields `StatusMappingID` and `RevocationComment` as normal.

3.10.2 Canceling jobs

To cancel all a user's jobs, pass an `ApplicantAction` of `CancelAllJobs`; for example:

```
<Actions>
  <ApplicantAction>CancelAllJobs</ApplicantAction>
</Actions>
```

Note: If the card is currently being processed by the bureau, the job is failed instead of canceled.

To cancel a single job, use an `ApplicantAction` of `CancelJob`, then include a `<Job>` node containing the ID of the job to cancel; for example:

```
<Actions>
  <ApplicantAction>CancelJob</ApplicantAction>
  <Job>12345</Job>
</Actions>
```

3.10.3 Filtering job cancellations

You can filter the jobs to be canceled – include an `ApplicantAction` of `CancelAllJobs`, then include a `Filters` node.

```
<Actions>
  <ApplicantAction>CancelAllJobs</ApplicantAction>
  <Filters>
    ...
  <Filters>
</Actions>
```

The `Filters` node has the following format:

```
<Filters>
  <Filter>
    <FieldName>xxx</FieldName>
    <FieldValue>xxx</FieldValue>
    <Operation>xxx</Operation>
  </Filter>
  ...
</Filters>
```

You can use the following in the `Operation` nodes:

- =
- !=
- gt
- lt
- ge
- le
- isnull
- notnull
- leftbracket
- rightbracket

Multiple filter nodes

You can include multiple `Filter` nodes. Each filter is added as an additional WHERE clause on the `vJobs` view to restrict the jobs. See the `vJobs` view in the MyID database for possible `FieldName` values.

By default, each `Filter` node is treated as an AND clause in the query; if you want to make the node an OR clause, include an `Or` node; for example:

```
<Filters>
  <Filter>
    <FieldName>ID</FieldName>
    <FieldValue>1024</FieldValue>
    <Operation>=</Operation>
  </Filter>
  <Filter>
    <FieldName>ID</FieldName>
    <FieldValue>1026</FieldValue>
    <Operation>=</Operation>
    <Or>true</Or>
  </Filter>
</Filters>
```

This example cancels jobs if they have an ID of 1024 or 1026.

Brackets and precedence

You can use the `leftbracket` and `rightbracket` operations on their own in a filter to add brackets and precedence to your query.

For example:

```
<Filters>
  <Filter>
    <FieldName>ID</FieldName>
    <FieldValue>1500</FieldValue>
    <Operation>!=</Operation>
  </Filter>
  <Filter>
    <Operation>leftbracket</Operation>
  </Filter>
  <Filter>
    <FieldName>ID</FieldName>
    <FieldValue>1000</FieldValue>
    <Operation>gt</Operation>
  </Filter>
  <Filter>
    <FieldName>ID</FieldName>
    <FieldValue>500</FieldValue>
    <Operation>lt</Operation>
    <Or>true</Or>
  </Filter>
  <Filter>
    <Operation>rightbracket</Operation>
  </Filter>
</Filters>
```

This example cancels all jobs with IDs above 1000 or below 500, except the job with ID 1500:

`ID != 1500 AND (ID > 1000 OR ID < 500)`

Therefore:

- Job 499 would be canceled.
- Job 500 would not be canceled.
- Job 999 would not be canceled.
- Job 1000 would not be canceled.

-
- Job 1001 would be canceled.
 - Job 1499 would be canceled.
 - Job 1500 would not be canceled.
 - Job 1501 would be canceled.
 - Job 9999 would be canceled.

You can nest multiple layers of `leftbracket` and `rightbracket` if necessary.

4

Calling the import service

The MyIDEnroll web service is installed by default to the following location:

`http://<myservername>/MyIDEnroll/MyIDEnroll.asmx`

The MyIDEnroll web service consists of the following methods:

- `CMSXMLWebImport` – used for standard systems.
- `PIVXMLWebImport` – used for PIV/FIPS 201 systems.
- `XMLImport` – used to import data using the `EdeficeData` schema. This option is deprecated.

These methods all take XML input parameters, and return an XML string representing the status of the operation.

See section [8, MyIDEnroll WSDL](#) for details of the WSDL for the web service.

4.1

Results

When the import service completes the import, it passes back an XML report containing information on whether the user's record was imported correctly.

See section [7.3, CMSImportReponse structure](#) for details of the XML schema used to return this report.

Section [7.6, PivImportResponse structure](#) contains the PIV version of the response schema.

Any errors (for example, if the XML document contains invalid characters) are returned as the response to the web service call. The errors are displayed as XML to make it easier for your system to parse them.

5 Advanced settings

To add these settings to your XML document, include a node called `Parameters` at the top level of the XML document.

For example:

```
<Parameters>
    <SourceID>Station1</SourceID>
    <IssueDate>2012-01-01</IssueDate>
    <GenerateUserDN>0</GenerateUserDN>
    <ActionOnDuplicate>REPLACE</ActionOnDuplicate>
    <RolesActionOnDuplicate>REPLACE</RolesActionOnDuplicate>
    <DeleteMissingUsers>0</DeleteMissingUsers>
    <PushToLDAP>1</PushToLDAP>
    <CreateUnknownGroups>1</CreateUnknownGroups>
    <AuditAll>1</AuditAll>
    <DataType>CMSRequestCard</DataType>
</Parameters>
```

Note: The parameters are described in the schema as a sequence, which means that the order is important.

The settings you can use are:

Parameter	Description
SourceID	The ID of the site.
IssueDate	The date the XML document was created.
GenerateUserDN	This option is deprecated. Set the value to 0.
ActionOnDuplicate	Determines what to do if the user already exists within MyID. The <code>LogonName</code> is used as the key to match user records. <code>REPLACE</code> – replace the existing user with the new details. <code>Merge</code> – merge the records. <code>MergeEmpty</code> – add only the field data that was previously empty; do not overwrite any previous data. <code>Skip</code> – abort the import. This generates an error.
RolesActionOnDuplicate	Determines what to do if the roles already exist within MyID. <code>REPLACE</code> or <code>Merge</code> – the user's roles and scope will be set to the roles indicated in the supplied XML, if a roles node is supplied. Any other roles held by the user will be removed. <code>MergeEmpty</code> – any roles not already held by the user will be added with the scope indicated. If the user already holds the role then the scope will be updated to reflect the supplied data. Any existing roles held by the user will not be removed. <code>Skip</code> – any roles not already held by the user will be added with the scope indicated. If the user already holds the role then it will not be altered. Any existing roles held by the user will not be removed.

Parameter	Description
DeleteMissingUsers	Deprecated. Always set to 0.
PushToLDAP	1 – add the user's details to the LDAP directory. 0 – do not add the user's details to the LDAP directory.
CreateUnknownGroups	Deprecated. Always set to 1.
AuditAll	1 – add all the audit information to the audit trail. 0 – do not add information to the audit trail.
DataType	Determines the specific behavior of the import service, including DN formats and transforms that will be used. CMSRequestCard – import a user's details and request a card. CMSUserUpdate – update an existing user. PIV – used for PIV card requests.
CheckImportResponseSchema	Set to 1 to prevent MyID from checking the returned XML against the response XML schema.
SynchronousImport	Deprecated. Do not use.
AllowBioImport	1 – allow the import of fingerprints. 0 – do not allow the import of fingerprints, but allow the import of face scans.
DefaultUserRole	If you do not specify the <code>Role\Name</code> , <code>Scope</code> and <code>LogonMechanism</code> in the <code>Applicant\Account\Roles</code> section of the import file, you can specify them here. Separate the role name, scope and logon mechanism with pipes (). For example: <code>Applicant Self Card</code> specifies the <code>Applicant</code> role, with a scope of <code>Self</code> , and a logon mechanism of <code>Card</code> .
DisallowCertificateSuspension	Set this value to 1, and when you cancel a user account using the Lifecycle API, MyID will not suspend the certificate, but uses the action associated with the <code>StatusMappingID</code> ; for example, a status mapping of 100 will permanently revoke the certificate. Set this value to 0 to suspend the certificate when you cancel the user account.
CardRequestThrottling	This option prevents the submission of multiple card requests if several requests are received in quick succession. Generating card requests like this can cause the bureau request mechanism to reuse the same FASC-N for more than once card request. Set this value to 1 to enable the throttling behavior. Set this value to 0, or omit the parameter, to disable the throttling behavior.

Parameter	Description
ReplaceUnassignedCards	Set to 1 to allow MyID to replace unassigned cards. Set to 0 to prevent MyID from replacing unassigned cards.

Note: On PIV systems, for PIV card requests you must set the `DataType` parameter as follows:

```
<DataType>PIV</DataType>
```

5.1 Custom schema and transform files

You can customize all Lifecycle API `xsd` and `xsl` schema and transform files by editing the web service configuration files. This allows you to override the schema and transform files provided with MyID with your own versions of those files; this means that you will not lose your schema and transform customizations when you update or upgrade your MyID installation.

To allow customizations to the schemas, add the following entries to MyIDEnrol web service `web.config` file:

```
<configSections>
<section name="MyIDSettings"
type="System.Configuration.DictionarySectionHandler"/>
</configSections>
<MyIDSettings configSource="myid.config" />
```

Once you have done this, you can add entries for schema and transform files to the `myid.config` file.

Add the key name and value name of the customized schema or transform file.

Note: All key names must be unique. For example:

```
<MyIDSettings>
  <add key="PIV" value="<Replacement schema for PivCardRequest.xsd>"></add>
  <add key="PIVRequestCard" value="<Replacement schema for
PivCardRequest.xsd>"></add>
  <add key="PIVApplicantEnrol" value="<Replacement schema for
PivApplicantUpdate.xsd>"></add>
  <add key="CMSRequestCard" value="<Replacement schema for
CMSCardRequest.xsd>"></add>
  <add key="CMSUpdateCard" value="<Replacement schema for
CMSUserUpdate.xsd>"></add>
  <add key="PIV2MyID" value="<Replacement transform for PIV2MyID.xsl>"></add>
  <add key="CMS2MyID" value="<Replacement transform for CMS2MyID.xsl>"></add>
  <add key="BOL2CMSSImportResponse" value="<Replacement transform for
BOL2CMSSImportResponse.xsl>"></add>
  <add key="BOL2PIVImportResponse" value="<Replacement transform for
BOL2PIVImportResponse.xsl>"></add>
</MyIDSettings>
```

Note: The names of the keys do not always match the names of the schema files. `PIV` and `PIVRequestCard` both override the `PivCardRequest.xsd` schema – do not specify both in the config file.

For example, if you want to override the `PivCardRequest.xsd` schema with your own version, which is called `MyPIVSchema.xsd`, you would add the following:

```
<MyIDSettings>
  <add key="PIVRequestCard" value="MyPIVSchema.xsd"></add>
</MyIDSettings>
```

If you also wanted to replace the standard PIV transform with your own version called MyPIVTransform.xsl:

```
<MyIDSettings>
  <add key="PIVRequestCard" value="MyPIVSchema.xsd"></add>
  <add key="PIV2MyID" value="MyPIVTransform.xsl"></add>
</MyIDSettings>
```

6 Troubleshooting

6.1 ASP.NET temporary folder permissions

If your MyID web service user does not have permissions to the .NET framework folder, you may see an error similar to the following:

The current identity "mydomain\myisuser" does not have write access to 'C:\WINDOWS\Microsoft.NET\Framework\v2.0.50727\Temporary ASP.NET Files'.

To grant access to the web service user, run the `aspnet_regiis` command in the .NET folder mentioned in the error message:

```
C:\WINDOWS\Microsoft.NET\Framework\v2.0.50727> aspnet_regiis -ga  
"mydomain\myuser"
```

Replace "mydomain\myuser" with your system's MyID web service user.

6.2 HTTP Error 500.24 – Internal Server Error

This error can occur when you have not configured the authentication mechanisms the MyIDEnroll web service and disabled the **ASP.NET Impersonation** option in IIS.

See section [2.2, Security settings](#) for details.

7 Data Structure

This section describes the structure of the data in the schemas.

The Lifecycle API uses the following XML schemas:

- MyIDBaseTypes
 - Contains the common schema type for all of the MyID Lifecycle API schemas.
- CMSSchemaTypes
 - Contains the common schema types for the CMSCardRequest and CMSUserUpdate schemas.
- CMSCardRequest
 - Use this schema to create your XML files containing user data to send to the XML web import service. This schema defines the necessary information that you have to include for the import to be successful.
- CMSUserUpdate
 - Use this schema to create your XML files containing user data when you are updating an existing user in the MyID database.
- CMSImportResponse
 - This is the schema used when the XML import service passes back information about the results of the user data import.
- PIVSchemaTypes
 - Contains the common schema types for the PIVCardRequest and PIVApplicantUpdate schemas.
- PIVCardRequest
 - Use this schema to create your XML files containing PIV user data to send to the XML web import service. This schema defines the necessary information that you have to include for the import to be successful.
- PIVApplicantUpdate
 - Use this schema to create your XML files containing user data when you are updating an existing PIV user in the MyID database.
- PIVImportResponse
 - This is the schema used when the XML import service passes back information about the results of the PIV user data import.

Note: Wherever a node is marked in the schema as a sequence, this order of the contents is important.

7.1 CMSCardRequest structure

This section describes the elements of the CMSCardRequest schema.

7.1.1 CMSCardRequest/Parameters

Contains the settings for the import. See section [5, Advanced settings](#).

7.1.2 CMSCardRequest/Group

Contains details of the Group to which the user will belong. If the group does not exist, MyID can create the group, depending on your `Parameters` settings.

7.1.3 CMSCardRequest/Group/Name

Used to identify the group.

If you are specifying an existing group, this is the only element you need to include to identify the group. If you are specifying a new group, you can complete the rest of the elements to provide the details for the new group.

Note: Group names must be unique. The import will fail if two different groups have the same name as the specified group name.

Note: If you specify a group that has been linked to an LDAP OU in MyID, any users associated with the group will be synchronized with the directory if MyID is configured for directory synchronization.

7.1.4 CMSCardRequest/Group/Description

The description of the group.

7.1.5 CMSCardRequest/Group/OrgUnit

The OU of the group.

7.1.6 CMSCardRequest/Group/Parent

The parent of the group.

Used for new groups only. This is the name of the group beneath which the specified group will be created. For new groups, if you do not specify a parent group, or the parent group does not exist, the new group is placed under the root. If you are specifying an existing group for the user, make sure you omit the `Parent` node.

Note: Parent group names must be unique. The import will fail if two different groups have the same name as the specified parent name.

7.1.7 CMSCardRequest/Group/AdditionalFields

Contains any extended group (`xg`) fields. See section [3.8, Importing additional fields](#) for details.

7.1.8 CMSCardRequest/Group/User

Contains the details for the user for whom the card is being requested.

You can import a single user in each XML document.

Note: You do not have to include a `User` node if you are importing the details of a group.

7.1.9 CMSCardRequest/Group/User/Personal

Contains the user's personal details.

7.1.10 CMSCardRequest/Group/User/Personal/FirstName

Internal name: `FirstName`

The user's first name.

7.1.11 CMSCardRequest/Group/User/Personal/LastName

Internal name: `Surname`

The user's last name.

Note: You must include one or both of `FirstName` and `LastName`. If you include both `FirstName` and `LastName`, make sure you specify them in that order – `FirstName` first, `LastName` immediately after. If you intend to supply only a `FirstName` or only a `LastName`, omit the other node – do not simply include an empty string.

7.1.12 CMSCardRequest/Group/User/Personal/Initial

Internal name: `Initial`

The user's middle initials.

7.1.13 CMSCardRequest/Group/User/Personal/Title

Internal name: `Title`

The user's title.

7.1.14 CMSCardRequest/Group/User/Personal/Email

Internal name: `Email`

The user's email address. This address is used for email notifications.

7.1.15 CMSCardRequest/Group/User/Personal/PhoneExt

Internal name: `PhoneExt`

The user's phone extension.

7.1.16 CMSCardRequest/Group/User/Personal/MobileNumber

Internal name: `MobileNumber`

The user's mobile phone number.

7.1.17 CMSCardRequest/Group/User/Personal/PhoneNumber

Internal name: `PhoneNumber`

The user's phone number.

7.1.18 CMSCardRequest/Group/User/Personal/EmployeeID

Internal name: EmployeeID

This should be a unique identifier for the applicant.

7.1.19 CMSCardRequest/Group/User/Personal/OptionalLine1

Internal name: OptionalLine1

Used to store extra information about the user.

7.1.20 CMSCardRequest/Group/User/Personal/OptionalLine2

Internal name: OptionalLine2

Used to store extra information about the user.

7.1.21 CMSCardRequest/Group/User/Personal/OptionalLine3

Internal name: OptionalLine3

Used to store extra information about the user.

7.1.22 CMSCardRequest/Group/User/Personal/OptionalLine4

Internal name: OptionalLine4

Used to store extra information about the user.

7.1.23 CMSCardRequest/Group/User/Authentication

Contains details of the security phrases to be used for the user.

Note: Currently, the schema does not provide validation on the `Authentication` element.

7.1.24 CMSCardRequest/Group/User/Authentication/SecurityPhrase

Contains a pair of elements – a `Prompt` and an `Answer` – that provide a security phrase for the applicant.

You can have up to five `SecurityPhrase` elements, each containing a `Prompt` and `Answer` pair.

Note: If you provide any security phrases for an existing user, *all* existing security phrases on that user's account are removed and replaced with the newly-provided security phrases. You can use this feature to delete the security phrases from a user's account – provide a single `Prompt` with an empty `Answer`, and the user's security phrases will be removed. (If the minimum number of security phrases is set to 1, the user will still be prompted for a security phrase when attempting to log on, but will be unable to authenticate.)

7.1.25 CMSCardRequest/Group/User/Authentication/SecurityPhrase/Prompt

Internal name: `Question` field in `SecurityQuestions`

Used to import a security question. If the question does not already exist, an entry is added to the `SecurityQuestions` table; this question will subsequently be available for use when setting security phrases in MyID.

The default security questions are:

ID	Question
1	Password
2	Mothers maiden name?
3	N.I number?
4	Favourite food?
5	Car registration number?
6	Name of pet
7	First school attended
8	An old phone number
9	A memorable date
10	A memorable place
11	A memorable event
12	A famous person
13	Place of birth
14	A country

ID	Question
15	A river
16	A movie
17	A song
18	A book
19	A sport
20	A postcode
21	An animal
22	First car type

7.1.26 CMSCardRequest/Group/User/Authentication/SecurityPhrase/Answer

Internal name: `SecurityPhrase` field in `UserSecurityQuestions`

Used to import an answer to a security question for an applicant. A hash of the answer is stored in the `UserSecurityQuestions` table.

Note: If you have set up the **Security Phrase Complexity** option within MyID to determine the complexity of security phrases, this is not enforced on any passwords that you import using the Lifecycle API.

You can encrypt the answer using a transport key – this allows you to maintain the security of the security phrase answer when you include it in the XML data.

To encrypt the answer:

1. Import your AES128 transport key into MyID using the **Key Manager** workflow.
2. External to MyID, encrypt the security phrase answer with the following settings:
 - Encode the security phrase answer as little-endian Unicode. Do not use a byte order mark.

For example, a security phrase of `answer` would be encoded as:

`0061006E0073007700650072`

- Pad the data using ISO9797 Method 2 (pad with a single 0x80, then 0x00 until the block-length is reached).
 - Encrypt using CBC or ECB mode encryption.
3. Add the hex-encoded encrypted data to the `Answer` node.
 4. Set the `KeyName` attribute of the `Answer` node to the name of the transport key you imported into MyID.

-
5. Set the `Mode` attribute of the `Answer` node to either `CBC` or `ECB`, depending on how you encrypted the answer.

For example:

- The transport key, `MyTransportKey`, has a value of:

206890FC9B4EA1D0137D8C692B3BFBCB6

- The security phrase is:

answer

- In the import, use the following:

```
<Answer KeyName="MyTransportKey" Mode="CBC">6713987B589F76BC4DA0F557D79A6275</Answer>
```

If you do not want to encrypt the answer in the XML document, omit the `KeyName` and `Mode` attributes. For example:

```
<Answer>plaintextanswer1234</Answer>
```

7.1.27 CMSCardRequest/Group/User/Card

Contains details of the card to be requested for the user.

7.1.28 CMSCardRequest/Group/User/Card/CardProfile

If present, this will request a card using the specified credential profile for this applicant. If performing an update, or the credential profile does not exist, no request will be made.

Note: Credential profiles were previously known as card profiles.

7.1.29 CMSCardRequest/Group/User/Card/CardExpiryDate

Used to specify the expiry date for the card when it is issued. The card will expire on the date specified, or on the date the credential profile specifies, whichever is earlier.

The format is `YYYY-MM-DD` – for example, `2016-12-25`.

Note: The card will expire at `00:00:00` UTC on the day of the expiry; that is, at the *start* of the day specified, not the *end*.

7.1.30 CMSCardRequest/Group/User/Card/Renewal

Used to specify whether the card is a renewal of an existing card. If the user already exists, you must set this option to `true` or card request jobs will not be created.

Can be one of the following values:

- `true` – this is a card renewal.
- `false` – this is not a card renewal.

7.1.31 CMSCardRequest/Group/User/Card/CardRequestedBy

This is the logon name of the person requesting the card. Used for auditing purposes.

7.1.32 CMSCardRequest/Group/User/Card/CancelExisting

Used to specify whether existing jobs of the same type are canceled when the new job is created. Include the empty node if you want to cancel the existing jobs:

```
<CancelExisting/>
```

If you omit this node, existing jobs will not be canceled when the new job is created.

7.1.33 CMSCardRequest/Group/User/Card/JobLabel

Used to specify a label for the job. You can use this label to search for and identify the job within MyID.

7.1.34 CMSCardRequest/Group/User/Card/Update

Used to specify the card being updated. You must make sure that the card is issued to the user.

If you do not specify the `OriginalSerialNumber` and `OriginalDeviceType` for the card to be updated, the card currently assigned to the user is used.

7.1.35 CMSCardRequest/Group/User/Card/Update/OriginalSerialNumber

The serial number of the card being updated. Used to target a specific card.

7.1.36 **CMSCardRequest/Group/User/Card/Update/OriginalDeviceType**

The device type of the card being updated.

7.1.37 **CMSCardRequest/Group/User/Card/Update/StatusMapping**

The status mapping code to be used when the card is updated.

See section [3.7.4, Status mapping codes](#) for details.

7.1.38 **CMSCardRequest/Group/User/Card/Replacement**

Used to specify the card to be replaced.

7.1.39 **CMSCardRequest/Group/User/Card/Replacement/OriginalSerialNumber**

The serial number of the card to be replaced. Mandatory if you specify the `Replacement` node.

7.1.40 **CMSCardRequest/Group/User/Card/Replacement/OriginalDeviceType**

The device type of the card to be replaced. Mandatory if you specify the `Replacement` node.

7.1.41 **CMSCardRequest/Group/User/Card/Replacement/StatusMapping**

Used to specify the status mapping ID for certificates on the credentials that are being replaced. This node is used when performing a replacement request; note that if you are performing a card replacement, you use `CMSCardRequest/Group/User/Card/StatusMapping` instead.

If you do not specify a `StatusMapping`, a status mapping ID of 1 – Lost – is used.

See section [3.7.4, Status mapping codes](#) for details.

7.1.42 CMSCardRequest/Group/User/Card/GenerateOTP

Note: This feature reserved for future use. It is not currently possible to use OTPs when collecting jobs. Do not use in the current version of MyID.

Used to generate a One-Time Password (OTP) for use when collecting the job created by the import request. If you specify this element, the user must provide the OTP when collecting the job. You can specify a notification mechanism to provide this OTP to the user by including a `Notification` node.

If you do not specify a `Notification` node, the OTP is sent to the user's email address using the **Job OTP** email template.

7.1.43 CMSCardRequest/Group/User/Card/GenerateOTP/Notification

Used to specify a notification method for OTPs.

7.1.44 CMSCardRequest/Group/User/Card/GenerateOTP/Notification/Name

The `Name` of the notification from the `Notifications` table in the MyID database.

Note: You must have notifications configured correctly within MyID. For more information, contact Intercede professional services.

7.1.45 CMSCardRequest/Group/User/Card/GenerateOTP/Notification/Action

Contains one of the following:

- `Event` – the notification is triggered once using the success data set up in the `Notifications` table. No further notifications are sent, even if the notification fails.
- `Success` – the notification is triggered using the success data set up in the `Notifications` table. If the notification fails, the back-up notifications set up in the fail data in the `Notifications` table are triggered.
- `Fail` – the notification is triggered using the fail data set up in the `Notifications` table. Multiple notifications are sent on a schedule specified by the `RetryDelays` in the `Notifications` table. You can use this option to force reminder notifications; the notification has not failed, but it is treated as a failed notification so that the retry system is triggered.

7.1.46 CMSCardRequest/Group/User/Card/OriginalSerialNumber

Used in conjunction with the `CMSCardRequest/Group/User/Card/OriginalDeviceType` node to specify a credential to be replaced. These settings also specify the credential profile to use when replacing the card. The credential profile used to issue this specified card is used to issue the new card. Alternatively, you can specify the credential profile using the `CMSCardRequest/Group/User/Card/CardProfile` node.

In addition, if you specify the `OriginalSerialNumber` and `OriginalDeviceType` for the card, all credentials on the same physical credential are marked as being replaced.

The `CMSCardRequest/Group/User/Card/StatusMapping` determines what happens to the certificates on the credentials that are being replaced.

7.1.47 CMSCardRequest/Group/User/Card/OriginalDeviceType

Used in conjunction with the `CMSCardRequest/Group/User/Card/OriginalSerialNumber` node to specify a credential to be replaced.

7.1.48 CMSCardRequest/Group/User/Card/SerialNumber

Used in conjunction with the `CMSCardRequest/Group/User/Card/DeviceType` node to specify an exact card to be issued.

7.1.49 CMSCardRequest/Group/User/Card/DeviceType

Used in conjunction with the `CMSCardRequest/Group/User/Card/SerialNumber` node to specify an exact card to be issued.

7.1.50 CMSCardRequest/Group/User/Card/StatusMapping

Used to specify the status mapping ID for certificates on the credentials that are being replaced. This node is used when performing a card request; note that if you are performing a card replacement, you use `CMSCardRequest/Group/User/Card/Replacement/StatusMapping` instead.

If you do not specify a `StatusMapping`, a status mapping ID of 1 – Lost – is used.

See section [3.7.4, Status mapping codes](#) for details.

7.1.51 CMSCardRequest/Group/User/Card/Reprovision

Reserved for future use.

7.1.52 CMSCardRequest/Group/User/Card/CardLayout

Optionally, contains the name of the card layout to use when printing the requested card.

The card layout name must be valid for the card's credential profile at the point that the card is issued; if the card layout name is not valid, the request will not be processed.

7.1.53 CMSCardRequest/Group/User/Card/AdditionalFields

Used to specify additional job (x_j) fields. Your system must already have been customized to set up these additional fields.

7.1.54 CMSCardRequest/Group/User/CardUpdate

Note: This `CardUpdate` node is reserved for future use. Do not use. You can use the `CMSCardRequest/Group/User/Card/Update` node instead.

The `CardUpdate` element contains details of card update requirements for existing cards.

7.1.55 CMSCardRequest/Group/User/CardUpdate/SerialNumber

Serial Number of the card to be updated.

7.1.56 CMSCardRequest/Group/User/CardUpdate/DeviceType

Device Type of card to be updated (for example, 'Oberthur v3').

7.1.57 CMSCardRequest/Group/User/CardUpdate/CardRequestedBy

The logon name of the person requesting the card update. Used for auditing purposes.

7.1.58 CMSCardRequest/Group/User/CardUpdate/ParametersXML

XML describing the card updates to be performed. Currently supports only `UnlockPIN`.

-
- 7.1.59 CMSCardRequest/Group/User/CardUpdate/ParametersXML/UnlockPIN
Set to 1 to unlock or set the PIN during the card update.
If you set this option to 1, the end user must enter and confirm a new PIN using the **Collect Card Update** workflow.
If the end user needs to carry out any operations (for example, adding a certificate) that require the card PIN, you must reset the card's PIN using this method before you do so; this is because the card was originally issued with a random, unknown PIN.
- 7.1.60 CMSCardRequest/Group/User/CardUpdate/PIN
Reserved for future use.
- 7.1.61 CMSCardRequest/Group/User/Account
Contains details of the user's account.
- 7.1.62 CMSCardRequest/Group/User/Account/DN
Internal name: `DistinguishedName`
The DN of the user's account in the LDAP.
- 7.1.63 CMSCardRequest/Group/User/Account/CN
Internal name: `CommonName`
- 7.1.64 CMSCardRequest/Group/User/Account/OU
Internal name: `OrganisationalUnit`
- 7.1.65 CMSCardRequest/Group/User/Account/UPN
Internal name: `UserPrincipalName`
- 7.1.66 CMSCardRequest/Group/User/Account/SAMAccountName
The SAM Account Name for the user.

7.1.67 CMSCardRequest/Group/User/Account/LogonName

Internal name: `LogonName`

The user's name, used to log into MyID. Must be unique.

A `LogonName` is required for all operations. If no value is supplied, the `CMSCardRequest/Group/User/Personal/EmployeeID` value is used instead. For new user imports, the `EmployeeID` is copied to the user's new `LogonName` record; for actions on existing users, the `EmployeeID` is used to match against the `LogonName`.

7.1.68 CMSCardRequest/Group/User/Account/NewLogonName

Note: This feature reserved for future use.

Allows you to specify a new logon name for the user.

7.1.69 CMSCardRequest/Group/User/Account/UniqueId

Maps onto the `objectGUID` attribute in Active Directory. When MyID synchronizes with the LDAP, it uses this `UniqueId` to map the users from MyID to the directory.

If your directory does not have an `objectGUID` attribute, the Distinguished Name for the user is used instead.

7.1.70 CMSCardRequest/Group/User/Account/Roles

Contains details of the MyID roles assigned to the user.

7.1.71 CMSCardRequest/Group/User/Account/Roles/Role

Contains details of the role you want to assign the applicant.

7.1.72 CMSCardRequest/Group/User/Account/Roles/Role/Name

Internal name: `UserProfile`

The name of the role.

7.1.73 CMSCardRequest/Group/User/Account/Roles/Role/Scope

Internal name: `Scope`

The scope of the role that the applicant is to have. The value must be one of the following:

- None
- Self
- Department
- Division
- All

7.1.74 CMSCardRequest/Group/User/Account/Roles/Role/LogonMechanism

Internal name: `LogonMechanism`

How the user must authenticate to gain that role. The value must be one of the following:

- Password
- Card

7.1.75 CMSCardRequest/Group/User/Account/EntrustProfile

Specifies an Entrust profile template to use for the applicant. If specified, the applicant is added to Entrust using the template.

7.1.76 CMSCardRequest/Group/User/Account/UserDataApproved

Internal name: `UserDataApproved`

Contains information on whether card issuance is approved for this applicant. Can be one of the following values:

- YES or 1
- NO or 0

If you set the card profile to have the **Require user data to be approved** option, you must set this option before the card can be issued. This flag confirms that the data being sent to MyID has passed all the enrollment checks required for card issuance.

7.1.77 **CMSCardRequest/Group/User/Photo**

Contains the applicant's photo.

7.1.78 **CMSCardRequest/Group/User/Photo/Encoding**

The type of data encoded in the block. This can be one of the following:

- `jpg` – JPG image data.
- `gif` – GIF image data.
- `png` – PNG image data.
- `bmp` – Windows bitmap image data.
- `378` – INCITS 378 fingerprint data.
- `385` – facial biometrics in ANSI/INCITS 385-2004 format.

For details of importing fingerprints or facial biometrics, contact customer support.

7.1.79 **CMSCardRequest/Group/User/Photo/Data**

A string of base64-encoded data containing the file to be uploaded.

7.1.80 **CMSCardRequest/Group/User/Photo/DateTaken**

The date of the data; for example, when the photograph was taken, or when the fingerprints were captured.

7.1.81 **CMSCardRequest/Group/User/Photo/Source**

The source of the data; for example, the type of biometric scanner.

7.1.82 CMSCardRequest/Group/User/Photo/None

Instead of providing a photograph, you can remove an existing user photograph and replace it with the `noImage.gif` default image.

To remove a user photograph, specify `_NULL_` in the `Photo` node; for example:

```
<Photo>
  <None>_NULL_</None>
<Photo>
```

Note: The image is removed from the user record, but is not removed from the MyID web server.

7.1.83 CMSCardRequest/Group/User/AdditionalFields

You can import information into additional extended user (`xu`) fields using the data import.

7.1.84 CMSCardRequest/Group/User/Actions

Contains actions to carry out for the applicant; for example, to remove or disable the user, or to cancel the user's credentials.

7.1.85 CMSCardRequest/Group/User/Actions/ApplicantAction

Perform an action on the user. If you do not supply an action in the `ApplicantAction` element, a suspended user will be unsuspended.

The possible actions are:

- `Disable` – disable the user's account.
- `Remove` – remove the user from the system.
- `CancelDevices` – Cancel all the user's credentials.
- `CancelDevice` – Cancel specific credentials. Specify the cards using the `CMSCardRequest/Group/User/Actions/Device` element.
- `CancelJob` – Cancel a specific job. Specify the job using the `CMSCardRequest/Group/User/Actions/Job` element.
- `CancelAllJobs` – Cancel all jobs for the specified user. You can also choose to cancel a subset of jobs by specifying a filter using the `CMSCardRequest/Group/User/Actions/Filters` element.
- `UnlockCard` – Unlock a card. Specify the card using the `CMSCardRequest/Group/User/Actions/Device` element.
- `RenewCertificate` – renew a certificate. Specify the certificate using `CMSCardRequest/Group/User/Actions/CertSerialNumber` and `CMSCardRequest/Group/User/Actions/CertPolicyName`.

7.1.86 CMSCardRequest/Group/User/Actions/CertSerialNumber

Used in conjunction with `CMSCardRequest/Group/User/Actions/CertPolicyName` to specify a certificate to renew.

7.1.87 CMSCardRequest/Group/User/Actions/CertPolicyName

Used in conjunction with `CMSCardRequest/Group/User/Actions/CertSerialNumber` to specify a certificate to renew.

7.1.88 CMSCardRequest/Group/User/Actions/StatusMappingID

The action to apply to the user. This should be an ID that matches an entry in the StatusMappings table. It controls how certificates are revoked.

7.1.89 CMSCardRequest/Group/User/Actions/RevocationComment

A free text description that is stored against revoked certificates in the database.

7.1.90 CMSCardRequest/Group/User/Actions/RevocationDelay

Used to specify a delay in days for the certificate revocation requests.

7.1.91 CMSCardRequest/Group/User/Actions/Device

Specifies the card to cancel when you have selected `CancelDevice` for the `ApplicantAction`, or the card to unlock when you have selected `UnlockCard` for the `ApplicantAction`.

Contains at least one `DeviceIdentifier` element – you can cancel multiple cards in a single request.

7.1.92 CMSCardRequest/Group/User/Actions/Device/DeviceIdentifier

Specifies the credential to be canceled or unlocked.

7.1.93 CMSCardRequest/Group/User/Actions/Device/DeviceIdentifier/SerialNumber

The serial number of the credential.

7.1.94 CMSCardRequest/Group/User/Actions/Device/DeviceIdentifier/SerialNumberField

The name of the field in which to look for the serial number. The field can be any field present in the `vDevices` view; for example, `SerialNumber` for the standard serial number or `HIDSerialNumber` for the HID serial number.

7.1.95 CMSCardRequest/Group/User/Actions/Device/ProcessStatus

Used to specify the process status to be used for the credential being cancelled.

You can use the following status codes, as listed in the `DeviceProcessStatuses` table in the database.

Status	Description
Active	Device is operational
Assigned	Device is assigned to a user but has not begun personalization
AtBureau	Device is at the bureau
Collected	Collected
Disposed	Disposed
Erasered	Erasered
Legacy	Legacy
Lost	Lost
None	None (Default the card may be re-issued)
Not Disposed	Not Collected
PendingActivation	Device is ready to be activated
PendingDeliveryConfirmation	Device has been dispatched from the bureau and is in transit
PendingPersonalisation	Device is ready to be personalized
Terminated	Card has been terminated
Unassigned	Device is not assigned to a user

7.1.96 CMSCardRequest/Group/User/Actions/RequestedBy

Used to specify the MyID logon name of the Initiator for any jobs created by the import process. If you do not specify a value here, the Initiator is set to `ImportProcessor`.

You can use the **Initiator** tab in the **Job Management** workflow to search for jobs created by specific users.

7.1.97 **CMSCardRequest/Group/User/Actions/Job**

Contains a the ID of a job to cancel. Used in conjunction with an `ApplicantAction` of `CancelJob`.

7.1.98 **CMSCardRequest/Group/User/Actions/Filters**

Used in conjunction with an `ApplicantAction` of `CancelAllJobs` to filter the list of jobs that are canceled.

See section [3.10.3, Filtering job cancellations](#) for details.

7.2 CMSUserUpdate structure

The `CMSUserUpdate` schema uses the same data elements as the `CMSCardRequest` schema. This schema requires less information as a minimum, however.

The following differences exist between the `CMSUserUpdate` and `CMSCardRequest` schema:

- The `CMSUserUpdate` schema allows you to specify a `User` block without including it in a `Group` block.
- The `CMSUserUpdate` schema does not have a `CardUpdate` element.
- The `CMSUserUpdate` schema does not have the following elements within the `Card` element:
 - ◆ `Renewal`
 - ◆ `CancelExisting`
 - ◆ `JobLabel`
 - ◆ `Replacement`
 - ◆ `GenerateOTP`
 - ◆ `OriginalSerialNumber`
 - ◆ `OriginalDeviceType`
 - ◆ `SerialNumber`
 - ◆ `DeviceType`
 - ◆ `StatusMapping`
 - ◆ `AdditionaFields`

7.3 CMSImportReponse structure

The CMSImportResponse schema is used when the XML import service passes back information about the results of the user data import. It contains blocks for the `Group` and the `User`.

7.3.1 CMSImportResponse/Group

Contains information about the group.

7.3.2 CMSImportResponse/Group/Name

Internal name: `Name`

Used to identify the group.

7.3.3 CMSImportResponse/Group/Result

The result of the import. Can be one of the following:

- `Created`
- `Already Exists`
- `Failed`

7.3.4 CMSImportResponse/Group/User

Contains information about the user.

7.3.5 CMSImportResponse/Group/User/FirstName

Internal name: `FirstName`

The first name of the user.

7.3.6 CMSImportResponse/Group/User/LastName

Internal name: `Surname`

The last name of the user.

7.3.7 CMSImportResponse/Group/User/EmployeeID

Internal name: `EmployeeID`

The Employee ID of the user.

7.3.8 CMSImportResponse/Group/User/LogonName

Internal name: `LogonName`

The MyID logon name of the user.

7.3.9 CMSImportResponse/Group/User/CardRequest

Internal name: `Jobs.ID`

The JobID for the card request. If there is no request, returns 0.

7.3.10 CMSImportResponse/Group/User/UnlockCardRequest

The JobID for the unlock card request. If there is no request, returns 0.

7.3.11 CMSImportResponse/Group/User/Result

The result of the import. Can be one of the following:

- Added
- Created
- Already Exists
- Failed
- Removed


-
- License Limit

7.3.12 CMSImportResponse/Group/User/error

Contains XML describing any errors that occurred during the import.

7.4 PivCardRequest

This section provides information on the structure of the XML data, including information on allowed values and the MyID internal name. Use this information in conjunction with the schemas and examples.



7.4.1 PivCardRequest/Parameters

See section [5, Advanced settings](#) for details.

7.4.2 PivCardRequest/Agency

The `Agency` element contains information about the applicant's agency, and contains the block for the applicant.

7.4.3 PivCardRequest/Agency/DeptCode

Internal name: `Xg16`

Encoded in the `PrintedInfo` block.

Mandatory only for Add; also mandatory for update if the agency is specified.

7.4.4 PivCardRequest/Agency/AgencyCode

Internal name: `Xg1`

Four alphanumeric characters. Encoded in the `FASCN` and in the `PrintedInfo` block.

Mandatory only for Add; also mandatory for update if the agency is specified.

7.4.5 PivCardRequest/Agency/FacilityCode

Internal name: `Xg2`

Encoded in the `FASCN` and in the `PrintedInfo` block.

Mandatory only for Add; also mandatory for update if the agency is specified.

7.4.6 PivCardRequest/Agency/AgencyName

Internal name: `Name` and `Xu3`

Used to identify the Agency. Also encoded in the DN for member Applicants.

Mandatory for Add; also mandatory for update if the agency is specified.

Note: Agency names must be unique. The import will fail if the agency name is not unique; this occurs even if a unique parent name is specified.

7.4.7 PivCardRequest/Agency/FacilityName

Not currently used.

7.4.8 PivCardRequest/Agency/DUNS

Internal name: `xg5`

Needed if the Organizational Category (below) is set to Commercial.

Mandatory only for Add; also mandatory for update if the agency is specified.

7.4.9 PivCardRequest/Agency/OC

Internal name: `xg3`

Organizational Category. Encoded in the FASCN.

An integer – the values map to the following categories:

- 1 – Federal
- 2 – State
- 3 – Commercial
- 4 – Foreign

Mandatory only for Add; also mandatory for update if the agency is specified.

7.4.10 PivCardRequest/Agency/OI

Internal name: `xg4`

Organizational Identifier. Encoded in the FASCN.

Mandatory only for Add; also mandatory for update if the agency is specified.

7.4.11 PivCardRequest/Agency/Department

Internal name: `xg17` and `xu54`

Encoded in the DN for member Applicants.

7.4.12 PivCardRequest/Agency/BaseDN

Internal name: `OrgUnit` and `Xg15`

If present, this is used as the default DN for member Applicants. The CN field is appended to this value.

7.4.13 PivCardRequest/Agency/Parent

Internal name: `Parent`

The name of the agency beneath which the specified agency should be positioned. For new agencies, if you do not specify a parent agency, or the parent agency does not exist, the new agency is placed under the root. If you are specifying an existing agency for the user, make sure you specify the correct parent agency, or omit the `Parent` node; otherwise, the agency will be moved under the new parent.

Note: Parent agency names must be unique. The import will fail if two different agencies have the same name as the specified parent name.

7.4.14 PivCardRequest/Agency/AgencyAddress

Used for delivery addresses. Contains the following elements:

Field Name	Internal Name
Address1	<code>Xg7</code>
Address2	<code>Xg8</code>
City	<code>Xg9</code>
State	<code>Xg10</code>
Zip	<code>Xg11</code>
PhoneNumber	<code>Xg13</code>
Country	<code>Xg12</code>
Email	<code>Xg14</code>
Contact	<code>Xg6</code>

7.4.15 PivCardRequest/Agency/AdditionalAgencyFields

Contains any extended (Xg) agency fields. See section [3.8.2, Additional group fields](#) for details.

7.4.16 PivCardRequest/Agency/Applicant

The Applicant element contains information about the applicant.

You can import a single applicant in each XML document.

7.4.17 PivCardRequest/Agency/Applicant/Personal

Contains the personal details of the applicant.

7.4.18 PivCardRequest/Agency/Applicant/Personal/FirstName

Internal name: FirstName

Mandatory.

7.4.19 PivCardRequest/Agency/Applicant/Personal/LastName

Internal name: Surname

Mandatory.

7.4.20 PivCardRequest/Agency/Applicant/Personal/NickName

Internal name: Xu49

7.4.21 PivCardRequest/Agency/Applicant/Personal/MiddleName

Internal name: Initial

7.4.22 PivCardRequest/Agency/Applicant/Personal/Suffix

Internal name: XuPIV4

7.4.23 PivCardRequest/Agency/Applicant/Personal/Title

Internal name: Title

7.4.24 PivCardRequest/Agency/Applicant/Personal/Email

Internal name: Email

This address is used for email notifications.

7.4.25 PivCardRequest/Agency/Applicant/Personal/Fax

Internal name: PhoneExt

7.4.26 PivCardRequest/Agency/Applicant/Personal/Cell

Internal name: MobileNumber

7.4.27 PivCardRequest/Agency/Applicant/Personal/Phone

Internal name: PhoneNumber

7.4.28 PivCardRequest/Agency/Applicant/Personal/EmployeeID

Internal name: EmployeeID

This should be a unique identifier for the applicant.

Mandatory.

Appears within MyID as the **Security** field on the **Edit PIV Applicant** workflow. For a PIV user (that is, a user who belongs to an agency that does not have a code of 9999) this value is used for the PI (Person Identifier) value in the FASC-N. Due to restrictions on the PI field in the FASC-N, this identifier must be a maximum of 10 numeric digits.

7.4.29 PivCardRequest/Agency/Applicant/Personal/Address

Used for delivery addresses. Contains the following elements:

- Address1
- Address2
- City
- StateZip

7.4.30 PivCardRequest/Agency/Applicant/Personal/BirthDate

Internal name: Xu37

Format: YYYY-MM-DD

7.4.31 PivCardRequest/Agency/Applicant/Personal/Nationality

Internal name: XuPIV1

A code referring to the nationality of the applicant. The possible values are:

Code	Nationality
AFG	Afghanistan
ALA	Aland Islands
ALB	Albania
DZA	Algeria
ASM	American Samoa
AND	Andorra
AGO	Angola
AIA	Anguilla
ATA	Antarctica
ATG	Antigua and Barbuda
ARG	Argentina
ARM	Armenia
ABW	Aruba
AUS	Australia
AUT	Austria
AZE	Azerbaijan
BHS	Bahamas
BHR	Bahrain
BGD	Bangladesh
BRB	Barbados

Code	Nationality
BLR	Belarus
BEL	Belgium
BLZ	Belize
BEN	Benin
BMU	Bermuda
BTN	Bhutan
BOL	Bolivia
BIH	Bosnia and Herzegovina
BWA	Botswana
BVT	Bouvet Island
BRA	Brazil
IOT	British Indian Ocean Territory
BRN	Brunei Darussalam
BGR	Bulgaria
BFA	Burkina Faso
BDI	Burundi
KHM	Cambodia
CMR	Cameroon
CAN	Canada
CPV	Cape Verde
CYM	Cayman Islands
CAF	Central African Republic
TCD	Chad
CHL	Chile
CHN	China
CXR	Christmas Island
CCK	Cocos (Keeling) Islands
COL	Colombia

Code	Nationality
COM	Comoros
COG	Congo
COD	Congo, Democratic Republic of the
COK	Cook Islands
CRI	Costa Rica
CIV	Cote d'Ivoire
HRV	Croatia
CUB	Cuba
CYP	Cyprus
CZE	Czech Republic
DNK	Denmark
DJI	Djibouti
DMA	Dominica
DOM	Dominican Republic
ECU	Ecuador
EGY	Egypt
SLV	El Salvador
GNQ	Equatorial Guinea
ERI	Eritrea
EST	Estonia
ETH	Ethiopia
FLK	Falkland Islands (Malvinas)
FRO	Faroe Islands
FJI	Fiji
FIN	Finland
FRA	France
GUF	French Guiana
PYF	French Polynesia

Code	Nationality
ATF	French Southern Territories
GAB	Gabon
GMB	Gambia
GEO	Georgia
DEU	Germany
GHA	Ghana
GIB	Gibraltar
GRC	Greece
GRL	Greenland
GRD	Grenada
GLP	Guadeloupe[2]
GUM	Guam
GTM	Guatemala
GGY	Guernsey
GIN	Guinea
GNB	Guinea-Bissau
GUY	Guyana
HTI	Haiti
HMD	Heard Island and McDonald Islands
VAT	Holy See (Vatican City State)
HND	Honduras
HKG	Hong Kong
HUN	Hungary
ISL	Iceland
IND	India
IDN	Indonesia
IRN	Iran, Islamic Republic of
IRQ	Iraq

Code	Nationality
IRL	Ireland
IMN	Isle of Man
ISR	Israel
ITA	Italy
JAM	Jamaica
JPN	Japan
JEY	Jersey
JOR	Jordan
KAZ	Kazakhstan
KEN	Kenya
KIR	Kiribati
PRK	Korea, Democratic People's Republic of
KOR	Korea, Republic of
KWT	Kuwait
KGZ	Kyrgyzstan
LAO	Lao People's Democratic Republic
LVA	Latvia
LBN	Lebanon
LSO	Lesotho
LBR	Liberia
LIB	Libyan Arab Jamahiriya
LIE	Liechtenstein
LTU	Lithuania
LUX	Luxembourg
MAC	Macao
MKD	Macedonia, the former Yugoslav Republic of
MDG	Madagascar
MWI	Malawi

Code	Nationality
MYS	Malaysia
MDV	Maldives
MLI	Mali
MLT	Malta
MHL	Marshall Islands
MTQ	Martinique
MRT	Mauritania
MUS	Mauritius
MYT	Mayotte
MEX	Mexico
FSM	Micronesia, Federated States of
MDA	Moldova, Republic of
MCO	Monaco
MNG	Mongolia
MNE	Montenegro
MSR	Montserrat
MAR	Morocco
MOZ	Mozambique
MMR	Myanmar
NAM	Namibia
NRU	Nauru
NPL	Nepal
NLD	Netherlands
ANT	Netherlands Antilles
NCL	New Caledonia
NZL	New Zealand
NIC	Nicaragua
NER	Niger

Code	Nationality
NGA	Nigeria
NIU	Niue
NFK	Norfolk Island
MNP	Northern Mariana Islands
NOR	Norway
OMN	Oman
PAK	Pakistan
PLW	Palau
PSE	Palestinian Territory, Occupied
PAN	Panama
PNG	Papua New Guinea
PRY	Paraguay
PER	Peru
PHL	Philippines
PCN	Pitcairn
POL	Poland
PRT	Portugal
PRI	Puerto Rico
QAT	Qatar
REU	Reunion
ROU	Romania
RUS	Russian Federation
RWA	Rwanda
SHN	Saint Helena
KNA	Saint Kitts and Nevis
LCA	Saint Lucia
SPM	Saint Pierre and Miquelon
VCT	Saint Vincent and the Grenadines

Code	Nationality
WSM	Samoa
SMR	San Marino
STP	Sao Tome and Principe
SAU	Saudi Arabia
SEN	Senegal
SRB	Serbia
SYC	Seychelles
SLE	Sierra Leone
SGP	Singapore
SVK	Slovakia
SVN	Slovenia
SLB	Solomon Islands
SOM	Somalia
ZAF	South Africa
SGS	South Georgia and the South Sandwich Islands
ESP	Spain
LKA	Sri Lanka
SDN	Sudan
SUR	Suriname
SJM	Svalbard and Jan Mayen
SWZ	Swaziland
SWE	Sweden
CHE	Switzerland
SYR	Syrian Arab Republic
TWN	Taiwan, Province of China
TJK	Tajikistan
TZA	Tanzania, United Republic of
THA	Thailand

Code	Nationality
TLS	Timor-Leste
TGO	Togo
TKL	Tokelau
TON	Tonga
TTO	Trinidad and Tobago
TUN	Tunisia
TUR	Turkey
TKM	Turkmenistan
TCA	Turks and Caicos Islands
TUV	Tuvalu
UGA	Uganda
UKR	Ukraine
ARE	United Arab Emirates
GBR	United Kingdom
USA	United States
UMI	United States Minor Outlying Islands
URY	Uruguay
UZB	Uzbekistan
VUT	Vanuatu
VEN	Venezuela
VNM	Viet Nam
VGB	Virgin Islands, British
VIR	Virgin Islands, U.S.
WLF	Wallis and Futuna
ESH	Western Sahara
YEM	Yemen

Code	Nationality
ZMB	Zambia
ZWE	Zimbabwe

7.4.32 PivCardRequest/Agency/Applicant/Personal/Citizenship

Reserved for future use. Do not use.

7.4.33 PivCardRequest/Agency/Applicant/Personal/CountryOfBirth

Internal name: XuPIV12.

Used for OPM Adjudication – contact customer support for more information, quoting reference SUP-123.

A two-character NCIC country code specifying the country of birth of the applicant. If the country is the United States of America, use the `PlaceOfBirth` node to specify the state.

7.4.34 PivCardRequest/Agency/Applicant/Personal/PlaceOfBirth

Reserved for future use.

7.4.35 PivCardRequest/Agency/Applicant/Personal/ExportRestrictions

Reserved for future use. Do not use.

7.4.36 PivCardRequest/Agency/Applicant/Authentication

Contains information about the security phrases for a user.

Note: Currently, the schema does not provide validation on the `Authentication` element.

7.4.37 PivCardRequest/Agency/Applicant/Authentication/SecurityPhrase

Contains a pair of elements – a `Prompt` and an `Answer` – that provide a security phrase for the applicant.

You can have up to five `SecurityPhrase` elements, each containing a `Prompt` and `Answer` pair.

Note: If you provide any security phrases for an existing user, *all* existing security phrases on that user's account are removed and replaced with the newly-provided security phrases. You can use this feature to delete the security phrases from a user's account – provide a single `Prompt` with an empty `Answer`, and the user's security phrases will be removed. (If the minimum number of security phrases is set to 1, the user will still be prompted for a security phrase when attempting to log on, but will be unable to authenticate.)

7.4.38 PivCardRequest/Agency/Applicant/Authentication/SecurityPhrase/Prompt

Internal name: `Question` field in `SecurityQuestions`

Used to import a security question. If the question does not already exist, an entry is added to the `SecurityQuestions` table; this question will subsequently be available for use when setting security phrases in MyID.

The default security questions are:

ID	Question
1	Password
2	Mothers maiden name?
3	N.I number?
4	Favourite food?
5	Car registration number?
6	Name of pet
7	First school attended
8	An old phone number
9	A memorable date
10	A memorable place
11	A memorable event
12	A famous person
13	Place of birth
14	A country

ID	Question
15	A river
16	A movie
17	A song
18	A book
19	A sport
20	A postcode
21	An animal
22	First car type

7.4.39 PivCardRequest/Agency/Applicant/Authentication/SecurityPhrase/Answer

Internal name: `SecurityPhrase` field in `UserSecurityQuestions`

Used to import an answer to a security question for an applicant. A hash of the answer is stored in the `UserSecurityQuestions` table.

Note: If you have set up the **Security Phrase Complexity** option within MyID to determine the complexity of security phrases, this is not enforced on any passwords that you import using the Lifecycle API.

You can encrypt the answer using a transport key – this allows you to maintain the security of the security phrase answer when you include it in the XML data.

You can encrypt the answer using a transport key – this allows you to maintain the security of the security phrase answer when you include it in the XML data.

To encrypt the answer:

Import your AES128 transport key into MyID using the **Key Manager** workflow.

- External to MyID, encrypt the security phrase answer with the following settings:
 - ◆ Encode the security phrase answer as little-endian Unicode. Do not use a byte order mark.

For example, a security phrase of `answer` would be encoded as:

`0061006E0073007700650072`

- ◆ Pad the data using ISO9797 Method 2 (pad with a single 0x80, then 0x00 until the block-length is reached).
- ◆ Encrypt using CBC or ECB mode encryption.

- Add the hex-encoded encrypted data to the `Answer` node.
- Set the `KeyName` attribute of the `Answer` node to the name of the transport key you imported into MyID.
- Set the `Mode` attribute of the `Answer` node to either `CBC` or `ECB`, depending on how you encrypted the answer.

For example:

- The transport key, `MyTransportKey`, has a value of:

206890FC9B4EA1D0137D8C692B3BFCB6

- The security phrase is:

answer

- In the import, use the following:

```
<Answer KeyName="MyTransportKey" Mode="CBC">6713987B589F76BC4DA0F557D79A6275</Answer>
```

If you do not want to encrypt the answer in the XML document, omit the `KeyName` and `Mode` attributes. For example:

```
<Answer>plaintextanswer1234</Answer>
```

7.4.40 PivCardRequest/Agency/Applicant/Card

Used to specify details for the applicant's card.

7.4.41 PivCardRequest/Agency/Applicant/Card/CardProfile

If present, this will request a card of the given name for this applicant. If performing an update, or the card profile does not exist, no request will be made.

7.4.42 PivCardRequest/Agency/Applicant/Card/CardExpiryDate

Used to specify the expiry date for the card when it is issued. The card will expire on the date specified, or on the date the card profile specifies, whichever is earlier.

The format is `YYYY-MM-DD` – for example, `2016-12-25`.

Note: The card will expire at `00:00:00` UTC on the day of the expiry; that is, at the *start* of the day specified, not the *end*.

7.4.43 PivCardRequest/Agency/Applicant/Card/Renewal

Used to specify whether the card is a renewal of an existing card. If the user already exists, you must set this option to `true` or card request jobs will not be created.

Can be one of the following values:

- `true` – this is a card renewal.
- `false` – this is not a card renewal.

7.4.44 PivCardRequest/Agency/Applicant/Card/CardRequestedBy

This is the logon name of the person requesting the card. Used for auditing purposes.

7.4.45 PivCardRequest/Agency/Applicant/Card/JobLabel

Allows you to specify a label for the renewal or replacement job. You can then search for this label in the **Job Management** or **Batch Issue Card** workflows.

7.4.46 PivCardRequest/Agency/Applicant/Card/Update

Used to specify the card being updated. You must make sure that the card is issued to the user.

If you do not specify the `OriginalSerialNumber` and `OriginalDeviceType` for the card to be updated, the card currently assigned to the user is used.

7.4.47 PivCardRequest/Agency/Applicant/Card/Update/OriginalSerialNumber

The serial number of the card being updated. Used to target a specific card.

7.4.48 PivCardRequest/Agency/Applicant/Card/Update/OriginalDeviceType

The device type of the card being updated.

7.4.49 PivCardRequest/Agency/Applicant/Card/Update/StatusMapping

The status mapping code to be used when the card is updated.

See section [3.7.4, Status mapping codes](#) for details.

7.4.50 PivCardRequest/Agency/Applicant/Card/Replacement

Allows you to provide the details of the credential being replaced.

7.4.51 PivCardRequest/Agency/Applicant/Card/Replacement/OriginalSerialNumber

The serial number of the card being replaced. Mandatory if you specify the `Replacement` node.

7.4.52 PivCardRequest/Agency/Applicant/Card/Replacement/OriginalDeviceType

The device type of the card being replaced. Mandatory if you specify the `Replacement` node.

Note: If you specify a valid serial number and device type for the card being replaced (that is, an existing credential that is currently assigned to the applicant) the original card is marked for cancellation and a new card request is created.

If the serial number is invalid (for example, the card does not exist, or is not assigned to any user) no card is marked for cancellation, but the replacement card is still requested.

If the serial number is valid but is assigned to another user, an error is generated; the card is not cancelled, and no replacement card is requested.

7.4.53 PivCardRequest/Agency/Applicant/Card/Replacement/StatusMapping

The status mapping ID for the replacement.

See section [3.7.4, Status mapping codes](#) for details.

7.4.54 PivCardRequest/Agency/Applicant/Card/Reprovision

Reserved for future use.

7.4.55 PivCardRequest/Agency/Applicant/Card/CardLayout

Optionally, contains the name of the card layout to use when printing the requested card.

The card layout name must be valid for the card's credential profile at the point that the card is issued; if the card layout name is not valid, the request will not be processed.

- 7.4.56 PivCardRequest/Agency/Applicant/Card/SerialNumber
Used in conjunction with the PivCardRequest/Agency/Applicant/Card/DeviceType node to specify an exact card to be issued.
Note: If you have the **Only Issue to Known Serial Numbers** option set in the credential profile, and you specify a serial number for the card that has not previously been added to MyID, the import will fail. This failure will be included in the audit.
- 7.4.57 PivCardRequest/Agency/Applicant/Card/DeviceType
Used in conjunction with the PivCardRequest/Agency/Applicant/Card/SerialNumber node to specify an exact card to be issued.
- 7.4.58 PivCardRequest/Agency/Applicant/Account
Contains details of the applicant's account.
- 7.4.59 PivCardRequest/Agency/Applicant/Account/DN
Internal name: DistinguishedName
The DN of the users account in the LDAP
- 7.4.60 PivCardRequest/Agency/Applicant/Account/AlternateDN
Internal name: Xu55
If populated this is used in preference to the DN for cert requests
- 7.4.61 PivCardRequest/Agency/Applicant/Account/CN
Internal name: CommonName
- 7.4.62 PivCardRequest/Agency/Applicant/Account/OU
Internal name: OrganisationalUnit
- 7.4.63 PivCardRequest/Agency/Applicant/Account/UPN
Internal name: UserPrincipalName

7.4.64 PivCardRequest/Agency/Applicant/Account/SAMAccountName

Internal name: SAMAccountName

Optional SAMAccountName value for the user. Maximum of 20 characters.

7.4.65 PivCardRequest/Agency/Applicant/Account/Domain

Internal name: Domain

Optional Domain value for the user. Maximum of 50 characters.

7.4.66 PivCardRequest/Agency/Applicant/Account/LogonName

Internal name: LogonName

User's name, used to log into MyID. Must be unique.

If no value is supplied, the PivCardRequest/Agency/Applicant/Personal/EmployeeID value is used instead.

7.4.67 PivCardRequest/Agency/Applicant/Account/Roles

Contains the details of the role you want to assign to the applicant. You can assign only one role to an applicant.

7.4.68 PivCardRequest/Agency/Applicant/Account/Roles/Role

Contains details of the role you want to assign the applicant. Contains the following elements:

Field Name	Internal Name	Description
Name	UserProfile	The name of the role that the applicant is to have. You must specify a role for the applicant.
Scope	Scope	The scope of the role that the applicant is to have. The value must be one of the following: None Self Department Division All

Field Name	Internal Name	Description
LogonMechanism	LogonMechanism	How the applicant must authenticate to gain that role. The value must be one of the following: Password Card

7.4.69 PivCardRequest/Agency/Applicant/Account/EntrustProfile

Specifies an Entrust profile template to use for the applicant. If specified, the applicant is added to Entrust using the template. See section [3.9, Importing users into Entrust](#) for details.

7.4.70 PivCardRequest/Agency/Applicant/Position

Contains information about the applicant's position within the agency.

7.4.71 PivCardRequest/Agency/Applicant/Position/EmployeeAssociation

Internal name: Xu4 and Xu5

If "Contractor" this is appended to the Applicant's DN. The numeric version stored in Xu4.

Note: This node *must* be populated with a valid lookup value for new user imports.

The value can be one of the following:

- Employee
- Civil Worker
- Executive
- Uniformed
- Contractor
- Affiliate
- Beneficiary

7.4.72 PivCardRequest/Agency/Applicant/Position/EmployeeAffiliation

Internal name: Xu53

Used for graphical personalization of the card.

7.4.73 PivCardRequest/Agency/Applicant/Position/Rank

Internal name: Xu1

Used for graphical personalization of the card.

The value is restricted to a list of codes (for example, E-1 or O-6). See the schema for a full list.

7.4.74 PivCardRequest/Agency/Applicant/Position/EmergencyRole

Internal name: Xu8

Can be used to allow additional card profiles to Emergency Responders.

Can be one of the following values:

- Law Enforcement
- Paramedic
- Doctor
- Firefighter
- Bomb Disposal
- Biohazard
- None

7.4.75 PivCardRequest/Agency/Applicant/Position/Privilege

Internal name: Xu30

These details are visible in **View Person** and during card issuance approval.

7.4.76 PivCardRequest/Agency/Applicant/Position/ApplicantPosition

Internal name: Xu11

These details are visible in **View Person** and during card issuance approval.

7.4.77 PivCardRequest/Agency/Applicant/Position/ExtraInfo

Internal name: Xu10

A free-text field to leave comments about an applicant.

7.4.78 PivCardRequest/Agency/Applicant/Sponsor

Contains information about the applicant's sponsor. These details are visible in **View Person** and during card issuance approval.

7.4.79 PivCardRequest/Agency/Applicant/Sponsor/SponsorName

Internal name: Xu31

7.4.80 PivCardRequest/Agency/Applicant/Sponsor/SponsorPosition

Internal name: Xu32

7.4.81 PivCardRequest/Agency/Applicant/Sponsor/SponsorAgency

Internal name: Xu34

7.4.82 PivCardRequest/Agency/Applicant/Sponsor/SponsorEmail

Internal name: Xu36

7.4.83 PivCardRequest/Agency/Applicant/Sponsor/SponsorPhoneNumber

Internal name: Xu35

7.4.84 PivCardRequest/Agency/Applicant/Biometry

Contains information about the applicant's biometric details. Some of these details are printed on the reverse of some card layouts. Also included in adjudication requests.

7.4.85 PivCardRequest/Agency/Applicant/Biometry/HeightInches

Internal name: Xu14

The applicant's height in inches.

Note: This must be numeric. For example, 73 is accepted; 73" or 6'1" or 6 foot 1 inch are not allowed.

7.4.86 PivCardRequest/Agency/Applicant/Biometry/WeightLbs

Internal name: Xu15

The applicant's weight in pounds.

Note: The schema allows a total of eight characters for this value; however, this includes the space and lbs that is appended during the import. Accordingly there are four characters available for the numeric part of the weight; for example, 9999, which becomes 9999 lbs when it is imported into MyID. Do not include the lbs in the import data. 140 is accepted; 140 lbs or 10 stone are not allowed.

7.4.87 PivCardRequest/Agency/Applicant/Biometry/Gender

Internal name: Xu38

7.4.88 PivCardRequest/Agency/Applicant/Biometry/EyeColor

Internal name: Xu13

The value of this element is restricted. See the schema for details.

7.4.89 PivCardRequest/Agency/Applicant/Biometry/HairColor

Internal name: Xu12

The value of this element is restricted. The current list is:

Code	Description
XXX	Unspecified or unknown
BAL	Bald
BLK	Black
BLN	Blonde or Strawberry
BLU	Blue
BRO	Brown
GRY	Gray or Partially Gray
GRN	Green
ONG	Orange
PNK	Pink
PLE	Purple
RED	Red or Auburn
SDY	Sandy
STR	Streaked
WHI	White

7.4.90 PivCardRequest/Agency/Applicant/Biometry/Race

Internal name: Xu39

The value of this element is restricted. See the schema for details.

7.4.91 PivCardRequest/Agency/Applicant/Biometry/BioSample

Contains elements to contain fingerprints, EFT data and facial biometric scans.

The possible elements are:

- `R_Little` – the right little finger. Uses the data type `BioFingerSample`.
- `R_Ring` – the right ring finger. Uses the data type `BioFingerSample`.
- `R_Middle` – the right middle finger. Uses the data type `BioFingerSample`.
- `R_Index` – the right index finger. Uses the data type `BioFingerSample`.
- `R_Thumb` – the right thumb. Uses the data type `BioFingerSample`.
- `L_Little` – the left little finger. Uses the data type `BioFingerSample`.
- `L_Ring` – the left ring finger. Uses the data type `BioFingerSample`.
- `L_Middle` – the left middle finger. Uses the data type `BioFingerSample`.
- `L_Index` – the left index finger. Uses the data type `BioFingerSample`.
- `L_Thumb` – the left thumb. Uses the data type `BioFingerSample`.
- `EFT` – the applicant's EFT sample. Uses the data type `EncodedData` with an encoding type of `bmp`. As this is a standard format, the encoding type is actually ignored.
- `FaceScan` – the applicant's facial biometric sample. Uses the data type `EncodedData` with an encoding type of `385`.
- `IrisScan` – the applicant's iris sample. Uses the data type `EncodedData` with an encoding type of `19794`.

BioFingerSample

The BioFingerSample block is used to provide the data for a single fingerprint. It contains either:

- An `EncodedData` block (see below), with the `Encoding` type of `378` and a `Data` block of `base64` data, and:
- An optional `RolledPrint` element, which can be either `Yes` or `No`, determining whether the fingerprint is a roll or a slap.
or:
- A `ReasonMissing` element, which can be either `Unprintable` or `Amputated`, if you cannot provide the data for the specified finger.

For example:

```
<BioSample>
    <R_Index>
        <Encoding>378</Encoding>
        <Data>Rk1SACAYMAAAgAAAAAAAAAAWgAxQDFAQAAAAAQgLQAfVUAgMkApaIAgJUAvV4A
gJMA1wEAgCkBBX4AgKkBIpIAgIkBLYQAgEMBOiYAgGoBPn8AgLABQY8AQIwAQrMA
QI4AYV0AQF0AiwwAQKMAkakAQLsAo08AQIkBF4YAAA=</Data>
        <RolledPrint>No</RolledPrint>
    </R_Index>
    <L_Index>
        <ReasonMissing>Unprintable</ReasonMissing>
    </L_Index>
...
</BioSample>
```

EncodedData

EncodedData blocks are used to include binary data in the imported XML; for example, fingerprint data, facial biometrics, and scanned documents. The EncodedData block has the following elements:

- Encoding – the type of data encoded in the block. This can be one of the following:
 - ◆ jpg – JPG image data.
 - ◆ gif – GIF image data.
 - ◆ png – PNG image data.
 - ◆ bmp – Windows bitmap image data.
 - ◆ 378 – INCITS 378 fingerprint data.
 - ◆ 385 – facial biometrics in ANSI/INCITS 385-2004 format.
 - ◆ 19794 – iris data.
- Data – a string of base64-encoded data containing the file to be uploaded.
- DateTaken – the date of the data; for example, when the photograph was taken, or when the fingerprints were captured.
Note: This is important for FIPS 201-2, as it lays down requirements for the maximum age of captured biometrics at the point of card issuance.
- Source – the source of the data; for example, the type of biometric scanner.

Removing and updating fingerprints

You can update the fingerprints for applicants by supplying new fingerprint data. Updated fingerprint data for the specified fingers overwrites the previously-recorded fingerprints. If you are using different fingers (for example, if the applicant has had their right index finger amputated) you can remove the existing fingerprints for specific fingers by including an empty `Data` node.

For example:

```
<BioSample>
    <R_Index>
        <Encoding>378</Encoding>
        <Data/>
    </R_Index>
</BioSample>
```

Alternatively, you can use the `ReasonMissing` element to remove existing fingerprints:

```
<BioSample>
    <R_Index>
        <ReasonMissing>Amputated</ReasonMissing>
    </R_Index>
</BioSample>
```

All changes to the fingerprints stored for applicants are recorded in the audit trail.

7.4.92 PivCardRequest/Agency/Applicant/Biometry/Signature

Contains the applicant's digitized signature. Uses type `EncodedData` with an `Encoding` type of `jpg`. See [EncodedData](#) on page 88 for details of the `EncodedData` format.

7.4.93 PivCardRequest/Agency/Applicant/IdentityDocs

Contains scans and information about the applicant's identity documents.

The following elements are included, one for each document:

- `IdentityDoc1`
- `IdentityDoc2`
- `SPF10`

Each document contains the following elements:

Field Name	Internal Name	Description	Allowed Values
Image		Contains the scanned document. Uses an EncodedData block with an Encoding type of jpg. See EncodedData on page 88 for details of the EncodedData format.	
Title	Xu21 Xu26	The type of the identity document	Restricted for IdentityDoc1 and IdentityDoc2 – see the schema for a list of supported documents. IDDocName1 is the list for the first identity document, and IDDocName2 is the list for the second identity document.
IssuedBy	Xu22 Xu27	The authority that issue the document	
Number	Xu23 Xu28	A unique identifier for the document	
Expiry	Xu24 Xu29	The expiry date for the document	YYYY-MM-DD

7.4.94 PivCardRequest/Agency/Applicant/NACI

Contains information about the applicant's NACI checks. The NACI checks are visible in the **View Person** workflow.

For example:

```
<NACI>
    <NACCCaseNumber>65522</NACCCaseNumber>
    <NACICaseNumber>65522</NACICaseNumber>
    <Check>
        <Type>SII</Type>
        <Status>AP</Status>
    </Check>
    <Check>
        <Type>DCII</Type>
        <Status>AP</Status>
    </Check>
    <Check>
        <Type>FBI Name</Type>
        <Status>AP</Status>
    </Check>
    <Check>
        <Type>FBI CHF</Type>
        <Status>AP</Status>
    </Check>
    <Check>
        <Type>NACI</Type>
        <Status>WR</Status>
    </Check>
    <CardIssuanceApproved>YES</CardIssuanceApproved>
    <Comments></Comments>
</NACI>
```

7.4.95 PivCardRequest/Agency/Applicant/NACI/NACCCaseNumber

Internal name: Xu40

7.4.96 PivCardRequest/Agency/Applicant/NACI/NACICaseNumber

Internal name: Xu46

7.4.97 PivCardRequest/Agency/Applicant/NACI/Check

Internal name: Xu41, Xu42, Xu43, Xu44, and Xu45

Contains one or more NACI background checks. You can have multiple `Check` elements in the import file. Each `Check` element contains the following elements:

- `Type` – The name of the background check. This can be one of the following:
 - ◆ SII
 - ◆ DCII
 - ◆ FBI Name
 - ◆ FBI CHF
 - ◆ NACI
- `Status` – the status of the NACI check. This can be one of the following:
 - ◆ NR – Not Required
 - ◆ WR – Waiting Response
 - ◆ AS – Assessing Response
 - ◆ AP – Approved
 - ◆ RJ – Rejected

7.4.98 PivCardRequest/Agency/Applicant/NACI/CardIssuanceApproved

Internal name: `UserDataApproved`

Contains information on whether card issuance is approved for this applicant. Can be one of the following values:

- YES or 1
- NO or 0

This flag confirms that the data being sent to MyID has passed all the enrollment checks required for card issuance. You must set this flag when adding an applicant for the first time, and also on card renewal.

Note: Throughout the [**PIV Integration Guide**](#), this field is referred to as the *User Data Approved* flag.

7.4.99 PivCardRequest/Agency/Applicant/NACI/Comments

Internal name: Xu33

Free text description, up to 255 characters, of any background checks.

7.4.100 PivCardRequest/Agency/Applicant/Photo

Contains the applicant's photo. This is an `EncodedData` type block, with an `Encoding` value of `jpg`, `gif`, `bmp` or `png`, and the `Data` block containing a base64-encoded image.

See [EncodedData](#) on page 88 for details of the `EncodedData` format.

7.4.101 PivCardRequest/Agency/Applicant/System

Contains system information for the application.

Required for PIV issuance.

7.4.102 PivCardRequest/Agency/Applicant/System/GUID

Internal name: Xu51

Unique ID used as part of the Card Holder Unique ID (CHUID).

Mandatory.

7.4.103 PivCardRequest/Agency/Applicant/System/CredNo

Internal name: Xu48

Credential Number – encoded in the FASC-N.

Mandatory.

7.4.104 PivCardRequest/Agency/Applicant/System/CS

Credential Series – always set to 1, but is ignored in the import anyway and the result is always 1. If you need to increment the credential series, contact customer support for details.

7.4.105 PivCardRequest/Agency/Applicant/System/POA

Legacy field – replaced by Applicant/EmployeeAssociation.

7.4.106 PivCardRequest/Agency/Applicant/System/ICI

Internal name: Xu47

The issue number of the next card to be issued. This is encoded in the FASCN. Recommend coding as a 1 always.

Mandatory only for Add.

7.4.107 PivCardRequest/Agency/Applicant/System/UserStatus

Internal name: Xu50

The state of the applicant in the process. This is displayed in the View Person workflow. Can be one of the following:

- Sponsored
- EnrollmentBegun
- EnrollmentComplete
- Vetting
- Escalated
- Approved
- CardRequested
- CardActivated
- Rejected

Note: The schema specifies a maximum of 50 characters, but the MyID limit is 40 characters.

7.4.108 PivCardRequest/Agency/Applicant/System/IssuanceNotifyURL

Internal name: Xu56

An override for the destination of the Card Issuance Notification XML that is sent when a card for the Applicant is issued.

Note: This notification is sent only when you issue a card through the MyID Desktop application. If you collect a card through the Self-Service App or Self-Service Kiosk, you must set up the Notifications table instead – see the [PIV Integration Guide](#) for details.

7.4.109 PivCardRequest/Agency/Applicant/System/CancelNotifyURL

Specifies an URL to be used for notifications for card cancellations. This allows you to specify a different URL for cancellations and issuance.

7.4.110 PivCardRequest/Agency/Applicant/System/CMSIssuanceNotifyURL

Specifies an URL to be used for notifications for card issuance. This allows you to specify a different URL for cancellations and issuance.

Note: Reserved for future use.

7.4.111 PivCardRequest/Agency/Applicant/AdditionalFields

You can import information into additional extended fields using the data import. See section [3.8.1, Additional user fields](#) for details.

7.4.112 PivCardRequest/Agency/Applicant/Actions

Contains actions to carry out for the applicant; for example, to remove or disable the user, or to cancel the user's credentials.

7.4.113 PivCardRequest/Agency/Applicant/Actions/ApplicantAction

Perform an action on the applicant. If you do not supply an action in the ApplicantAction element, a suspended applicant will be unsuspended.

The possible actions are:

- `Disable` – disable the user's account.
- `Remove` – remove the user from the system.
- `CancelDevices` – cancel all the user's credentials.
- `CancelDevice` – cancel specific credentials. Specify the credentials using the `Device` element.

- CancelJob – Cancel a specific job. Specify the job using the `PivCardRequest/Agency/Applicant/Actions/Job` element.
- CancelAllJobs – Cancel all jobs for the specified user. You can also choose to cancel a subset of jobs by specifying a filter using the `CMSCardRequest/Group/User/Actions/Filters` element.
- RenewCertificate – renew a certificate. Specify the certificate using `PivCardRequest/Agency/Applicant/Actions/CertSerialNumber` and `PivCardRequest/Agency/Applicant/Actions/CertPolicyName`.

7.4.114 `PivCardRequest/Agency/Applicant/Actions/CertSerialNumber`

Used in conjunction with an `ApplicantAction` of `RenewCertificate` and `PivCardRequest/Agency/Applicant/Actions/CertPolicyName` to specify a certificate to renew.

7.4.115 `PivCardRequest/Agency/Applicant/Actions/CertPolicyName`

Used in conjunction with an `ApplicantAction` of `RenewCertificate` and `PivCardRequest/Agency/Applicant/Actions/CertSerialNumber` to specify a certificate to renew.

7.4.116 `PivCardRequest/Agency/Applicant/Actions/StatusMappingID`

The action to apply to the user. This should be an ID that matches an entry in the `StatusMappings` table. It controls how certificates are revoked.

Note: You cannot specify negative IDs from the `StatusMappings` table – these are reserved for system use.

7.4.117 `PivCardRequest/Agency/Applicant/Actions/RevocationComment`

A free text description that is stored against revoked certificates in the database.

7.4.118 `PivCardRequest/Agency/Applicant/Actions/Device`

Specifies the credential (for example, a smart card) to cancel when you have selected `CancelDevice` for the `ApplicantAction`. Contains at least one `DeviceIdentifier` element. You can specify more than one credential to cancel by including multiple `DeviceIdentifier` elements.

7.4.119 `PivCardRequest/Agency/Applicant/Actions/Device/DeviceIdentifier`

Specifies the credential to be canceled or unlocked.

7.4.120 **PivCardRequest/Agency/Applicant/Actions/Device/DeviceIdentifier/SerialNumber**

The serial number of the credential.

7.4.121 **PivCardRequest/Agency/Applicant/Actions/Device/DeviceIdentifier/SerialNumberField**

The name of the field in which to look for the serial number. The field can be any field present in the `vDevices` view; for example, `SerialNumber` for the standard serial number or `HIDSerialNumber` for the HID serial number.

7.4.122 **PivCardRequest/Agency/Applicant/Actions/Device/ProcessStatus**

Used to specify the process status to be used for the credential being cancelled.

You can use the following status codes, as listed in the `DeviceProcessStatuses` table in the database.

Status	Description
Active	Device is operational
Assigned	Device is assigned to a user but has not begun personalization
AtBureau	Device is at the bureau
Collected	Collected
Disposed	Disposed
Erasered	Erasered
Legacy	Legacy
Lost	Lost
None	None (Default the card may be re-issued)
Not Disposed	Not Collected
PendingActivation	Device is ready to be activated
PendingDeliveryConfirmation	Device has been dispatched from the bureau and is in transit
PendingPersonalisation	Device is ready to be personalized
Terminated	Card has been terminated
Unassigned	Device is not assigned to a user

7.4.123 PivCardRequest/Agency/Applicant/Actions/Job

Contains a the ID of a job to cancel. Used in conjunction with an `ApplicantAction` of `CancelJob`.

7.5 PivApplicantUpdate structure

The PivApplicantUpdate schema uses the same data elements as the PivCardRequest schema. This schema requires less information as a minimum, however. See the schema for details of the minimum data required.

For example:

- `PivCardRequest/Agency/Applicant/Sponsor` is mandatory for PivCardRequest.
- `PivCardRequest/Agency/Applicant/Sponsor/SponsorName` is mandatory for PivCardRequest.
- `PivCardRequest/Agency/Applicant/Sponsor/SponsorAgency` is mandatory for PivCardRequest.
- `PivCardRequest/Agency/Applicant/System/GUID` is mandatory for PivCardRequest.
- `PivCardRequest/Agency/Applicant/System/CredNo` is mandatory for PivCardRequest.
- `PivCardRequest/Agency/Applicant/System/ICI` is mandatory for PivCardRequest.

7.6 PivImportResponse structure

The PivImportResponse schema is used when the XML import service passes back information about the results of the applicant data import.. It contains blocks for the `Agency` and the `Applicant`.

7.6.1 PivImportResponse/Agency

Contains information about the agency.

7.6.2 PivImportResponse/Agency/AgencyName

Internal name: `Name` and `Xu3`

Used to identify the Agency. Also encoded in the DN for member Applicants.

7.6.3 PivImportResponse/Agency/AgencyCode

Internal name: `Xg1`

Four alphanumeric characters. Encoded in the FASCN and in the PrintedInfo block.

7.6.4 PivImportResponse/Agency/Result

The result of the import for the agency. Can be one of the following:

- Created
- Already Exists
- Failed

7.6.5 PivImportResponse/Agency/Applicant

Contains information about the applicant.

7.6.6 PivImportResponse/Agency/Applicant/FirstName

Internal name: `FirstName`

The applicant's first name.

7.6.7 PivImportResponse/Agency/Applicant/LastName

Internal name: `Surname`

The applicant's last name.

7.6.8 PivImportResponse/Agency/Applicant/EmployeeID

Internal name: `EmployeeID`

This is a unique, numerical identifier for the applicant.

7.6.9 PivImportResponse/Agency/Applicant/CardRequest

Internal name: `Jobs.ID`

The JobID for the card request. If there is no request, returns 0.

7.6.10 PivImportResponse/Agency/Applicant/CardRequestFailReason

The reason the card request failed.

7.6.11 PivImportResponse/Agency/Applicant/Result

The result of the import for the applicant. Can be one of the following:

- Added
- Already Exists
- Failed
- Removed
- License Limit

8 MyIDEnroll WSDL

The WSDL definition for the MyIDEnroll web service is as follows:

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:tm="http://microsoft.com/wsdl/mime/textMatching/"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:mime="http://schemas.xmlsoap.org/wsdl/mime/"
  xmlns:tns="http://www.intercede.com/MyIDEnroll" xmlns:s="http://www.w3.org/2001/XMLSchema"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/" xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
  targetNamespace="http://www.intercede.com/MyIDEnroll" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <s:schema elementFormDefault="qualified" targetNamespace="http://www.intercede.com/MyIDEnroll">
      <s:element name="PIVXMLWebImport">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="xmlIn" type="s:string" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:element name="PIVXMLWebImportResponse">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="PIVXMLWebImportResult" type="s:string" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:element name="CMSXMLWebImport">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="xmlIn" type="s:string" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:element name="CMSXMLWebImportResponse">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="CMSXMLWebImportResult" type="s:string" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:element name="XMLImport">
        <s:complexType>
          <s:sequence>
```

```
<s:element minOccurs="0" maxOccurs="1" name="ParametersXML" type="s:string" />
<s:element minOccurs="0" maxOccurs="1" name="xmlData" type="s:string" />
</s:sequence>
</s:complexType>
</s:element>
<s:element name="XMLImportResponse">
<s:complexType>
<s:sequence>
<s:element minOccurs="0" maxOccurs="1" name="XMLImportResult" type="s:string" />
</s:sequence>
</s:complexType>
</s:element>
</s:schema>
</wsdl:types>
<wsdl:message name="PIVXMLWebImportSoapIn">
<wsdl:part name="parameters" element="tns:PIVXMLWebImport" />
</wsdl:message>
<wsdl:message name="PIVXMLWebImportSoapOut">
<wsdl:part name="parameters" element="tns:PIVXMLWebImportResponse" />
</wsdl:message>
<wsdl:message name="CMSXMLWebImportSoapIn">
<wsdl:part name="parameters" element="tns:CMSXMLWebImport" />
</wsdl:message>
<wsdl:message name="CMSXMLWebImportSoapOut">
<wsdl:part name="parameters" element="tns:CMSXMLWebImportResponse" />
</wsdl:message>
<wsdl:message name="XMLImportSoapIn">
<wsdl:part name="parameters" element="tns:XMLImport" />
</wsdl:message>
<wsdl:message name="XMLImportSoapOut">
<wsdl:part name="parameters" element="tns:XMLImportResponse" />
</wsdl:message>
<wsdl:portType name="MyIDEnrollSoap">
<wsdl:operation name="PIVXMLWebImport">
<wsdl:input message="tns:PIVXMLWebImportSoapIn" />
<wsdl:output message="tns:PIVXMLWebImportSoapOut" />
</wsdl:operation>
<wsdl:operation name="CMSXMLWebImport">
<wsdl:input message="tns:CMSXMLWebImportSoapIn" />
<wsdl:output message="tns:CMSXMLWebImportSoapOut" />
</wsdl:operation>
<wsdl:operation name="XMLImport">
<wsdl:input message="tns:XMLImportSoapIn" />
<wsdl:output message="tns:XMLImportSoapOut" />
```

```
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="MyIDEnrollSoap" type="tns:MyIDEnrollSoap">
  <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="PIVXMLWebImport">
    <soap:operation soapAction="http://www.intercede.com/MyIDEnroll/PIVXMLWebImport" style="document" />
    <wsdl:input>
      <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="CMSXMLWebImport">
    <soap:operation soapAction="http://www.intercede.com/MyIDEnroll/CMSXMLWebImport" style="document" />
    <wsdl:input>
      <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="XMLImport">
    <soap:operation soapAction="http://www.intercede.com/MyIDEnroll/XMLImport" style="document" />
    <wsdl:input>
      <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
</wsdl:binding>
<wsdl:binding name="MyIDEnrollSoap12" type="tns:MyIDEnrollSoap">
  <soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="PIVXMLWebImport">
    <soap12:operation soapAction="http://www.intercede.com/MyIDEnroll/PIVXMLWebImport" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="CMSXMLWebImport">
```

```
<soap12:operation soapAction="http://www.intercede.com/MyIDEnroll/CMSXMLWebImport" style="document" />
<wsdl:input>
  <soap12:body use="literal" />
</wsdl:input>
<wsdl:output>
  <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="XMLImport">
  <soap12:operation soapAction="http://www.intercede.com/MyIDEnroll/XMLImport" style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="MyIDEnroll">
  <wsdl:port name="MyIDEnrollSoap" binding="tns:MyIDEnrollSoap">
    <soap:address location="http://localhost/MyiDENroll/MyIDEnroll.asmx" />
  </wsdl:port>
  <wsdl:port name="MyIDEnrollSoap12" binding="tns:MyIDEnrollSoap12">
    <soap12:address location="http://localhost/MyiDENroll/MyIDEnroll.asmx" />
  </wsdl:port>
</wsdl:service>
</wsdl:definitions>
```

9 XML schemas

This section contains listings of the Lifecycle schemas available.

9.1 Schema file locations

The schema files are installed to the `Schemas` folder the `MyIDEnroll` folder on the `MyID` web server; by default, this is:

```
C:\Program Files (x86)\Intercede\MyID\Web\MyIDEnroll\Schemas
```

9.2 MyIDBaseTypes

This schema contains the elements common to all the MyID Lifecycle API schemas.

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    targetNamespace="http://www.intercede.com/CommonTypes"
    elementFormDefault="qualified" attributeFormDefault="qualified"
>
    <xs:simpleType name="String30">
        <xs:restriction base="xs:string">
            <xs:maxLength value="30"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="String80">
        <xs:restriction base="xs:string">
            <xs:maxLength value="80"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="String100">
        <xs:restriction base="xs:string">
            <xs:maxLength value="100"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="String120">
        <xs:restriction base="xs:string">
            <xs:maxLength value="120"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="String200">
        <xs:restriction base="xs:string">
            <xs:maxLength value="200"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="String255">
        <xs:restriction base="xs:string">
            <xs:maxLength value="255"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="String2">
        <xs:restriction base="xs:string">
            <xs:maxLength value="2"/>
        </xs:restriction>
    </xs:simpleType>
```

```
</xs:restriction>
</xs:simpleType>
<xs:simpleType name="String20">
  <xs:restriction base="xs:string">
    <xs:maxLength value="20"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String8">
  <xs:restriction base="xs:string">
    <xs:maxLength value="8"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String40">
  <xs:restriction base="xs:string">
    <xs:maxLength value="40"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String50">
  <xs:restriction base="xs:string">
    <xs:maxLength value="50"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String64">
  <xs:restriction base="xs:string">
    <xs:maxLength value="64"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String10">
  <xs:restriction base="xs:string">
    <xs:maxLength value="10"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String1">
  <xs:restriction base="xs:string">
    <xs:maxLength value="1"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String3">
  <xs:restriction base="xs:string">
    <xs:maxLength value="3"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String4">
  <xs:restriction base="xs:string">
```

```
    <xs:maxLength value="4"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String6">
  <xs:restriction base="xs:string">
    <xs:maxLength value="6"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="StringBase64">
  <xs:restriction base="xs:string">
    <xs:pattern value="[a-zA-Z0-9+ /=\n\r\w\t]*"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="Int50">
  <xs:restriction base="xs:string">
    <xs:maxLength value="50"/>
    <xs:pattern value="[0-9]*"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="Int1">
  <xs:restriction base="xs:string">
    <xs:maxLength value="1"/>
    <xs:pattern value="[0-9]"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="Int4">
  <xs:restriction base="xs:string">
    <xs:maxLength value="4"/>
    <xs:pattern value="[0-9]*"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="Int9">
  <xs:restriction base="xs:string">
    <xs:maxLength value="9"/>
    <xs:pattern value="[0-9]*"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="YesNo">
  <xs:restriction base="xs:string">
    <xs:enumeration value="YES"/>
    <xs:enumeration value="NO"/>
```

```
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="YesNoOneZero">
<xs:restriction base="xs:string">
<xs:enumeration value="YES"/>
<xs:enumeration value="NO"/>
<xs:enumeration value="1"/>
<xs:enumeration value="0"/>
</xs:restriction>
</xs:simpleType>

<xs:complexType name="EncryptedData">
<xs:simpleContent>
<xs:extension base="xs:string">
<xs:attribute name="KeyName" type="xs:string" use="optional" />
<xs:attribute name="Mode" type="xs:string" use="optional" />
</xs:extension>
</xs:simpleContent>
</xs:complexType>

<xs:simpleType name="OperationType">
<xs:restriction base="xs:string">
<xs:enumeration value="=" />
<xs:enumeration value="!=" />
<xs:enumeration value="gt" />
<xs:enumeration value="lt" />
<xs:enumeration value="ge" />
<xs:enumeration value="le" />
<xs:enumeration value="isnull" />
<xs:enumeration value="notnull" />
<xs:enumeration value="leftbracket" />
<xs:enumeration value="rightbracket" />
</xs:restriction>
</xs:simpleType>

</xs:schema>
```

9.3 CMS Schema Types

This schema contains the elements common to the CMSCardRequest and CMSUserUpdate schemas.

```
<?xml version="1.0"?>
<xs:schema>
```

```
xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:myidbase="http://www.intercede.com/CommonTypes"
targetNamespace="http://www.intercede.com/MyIDSchema/CMSCardRequest"
xmlns="http://www.intercede.com/MyIDSchema/CMSCardRequest"
elementFormDefault="qualified" attributeFormDefault="qualified"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
>

<xs:import namespace="http://www.intercede.com/CommonTypes" schemaLocation="MyIDBaseTypes.xsd"/>

<xs:complexType name="ParametersBlockType">
    <xs:all>
        <xs:element name="SourceID" type="xs:string" minOccurs="1" maxOccurs="1"/>
        <xs:element name="IssueDate" type="xs:date" minOccurs="0" maxOccurs="1"/>
        <xs:element name="GenerateUserDN" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
        <xs:element name="ActionOnDuplicate" type="xs:string" minOccurs="1" maxOccurs="1"/>
        <xs:element name="RolesActionOnDuplicate" type="xs:string" minOccurs="1" maxOccurs="1"/>
        <xs:element name="DeleteMissingUsers" type="xs:unsignedInt" minOccurs="1" maxOccurs="1"/>
        <xs:element name="PushToLDAP" type="xs:unsignedInt" minOccurs="1" maxOccurs="1"/>
        <xs:element name="CreateUnknownGroups" type="xs:unsignedInt" minOccurs="1" maxOccurs="1"/>
        <xs:element name="AuditAll" type="myidbase:Int1" minOccurs="1" maxOccurs="1"/>
        <xs:element name="DataType" type="xs:string" minOccurs="0" maxOccurs="1"/>
        <xs:element name="CheckImportResponseSchema" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
        <xs:element name="SynchronousImport" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
        <xs:element name="AllowBioImport" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
        <xs:element name="DefaultUserRole" type="xs:string" minOccurs="0" maxOccurs="1"/>
        <xs:element name="DisallowCertificateSuspension" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
        <xs:element name="CardRequestThrottling" type="xs:unsignedInt" minOccurs="0" maxOccurs="1"/>
        <xs:element name="ReplaceUnassignedCards" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
    </xs:all>
</xs:complexType>

<xs:complexType name="PersonalBlockType">
    <xs:sequence>
        <xs:choice>
            <xs:sequence>
                <xs:element name="FirstName" type="myidbase:NotEmptyString64" minOccurs="1" maxOccurs="1"/>
                <xs:element name="LastName" type="myidbase:NotEmptyString64" minOccurs="0" maxOccurs="1"/>
            </xs:sequence>
            <xs:element name="LastName" type="myidbase:NotEmptyString64" minOccurs="1" maxOccurs="1"/>
        </xs:choice>
        <xs:element name="Initial" type="myidbase:String40" minOccurs="0" maxOccurs="1"/>
        <xs:element name="Title" type="myidbase:String20" minOccurs="0" maxOccurs="1"/>
        <xs:element name="Email" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>
```

```
<xs:element name="PhoneExt" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<xs:element name="MobileNumber" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<xs:element name="PhoneNumber" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<xs:element name="EmployeeID" type="myidbase:String50" minOccurs="1" maxOccurs="1"/>
<xs:element name="OptionalLine1" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="OptionalLine2" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="OptionalLine3" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="OptionalLine4" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="AuthenticationBlockType">
<xs:sequence>
<xs:element name="SecurityPhrase" minOccurs="0" maxOccurs="unbounded">
<xs:complexType>
<xs:sequence>
<xs:element name="Prompt" type="myidbase:NotEmptyString255" minOccurs="1" maxOccurs="1"/>
<xs:element name="Answer" type="myidbase:EncryptedData" minOccurs="1" maxOccurs="1"/>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>

<xs:complexType name="UpdateCardBlockType">
<xs:sequence>
<xs:element name="OriginalSerialNumber" type="myidbase:String50" minOccurs="1" maxOccurs="1" />
<xs:element name="OriginalDeviceType" type="myidbase:String50" minOccurs="1" maxOccurs="1" />
<xs:element name="StatusMapping" type="xs:int" minOccurs="0" maxOccurs="1"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="ReplacementCardBlockType">
<xs:all>
<xs:element name="OriginalSerialNumber" type="myidbase:String50" minOccurs="1" maxOccurs="1"/>
<xs:element name="OriginalDeviceType" type="myidbase:String50" minOccurs="1" maxOccurs="1" />
<xs:element name="StatusMapping" type="xs:int" minOccurs="0" maxOccurs="1"/>
</xs:all>
</xs:complexType>

<xs:complexType name="CardUpdateBlockType">
<xs:all>
<xs:element name="SerialNumber" type="myidbase:String255" minOccurs="1" maxOccurs="1"/>
<xs:element name="DeviceType" type="myidbase:String255" minOccurs="1" maxOccurs="1"/>
```

```
<xs:element name="CardRequestedBy" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="ParametersXML" type="JobParameters" minOccurs="1" maxOccurs="1"/>
<xs:element name="PIN" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
</xs:all>
</xs:complexType>

<xs:complexType name="AccountBlockType">
<xs:sequence>
<xs:element name="DN" type="myidbase:String1024" minOccurs="0" maxOccurs="1"/>
<xs:element name="CN" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="OU" type="myidbase:String1024" minOccurs="0" maxOccurs="1"/>
<xs:element name="UPN" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="SAMAccountName" type="myidbase:String20" minOccurs="0" maxOccurs="1"/>
<xs:element name="Domain" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<xs:element name="LogonName" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="NewLogonName" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="UniqueID" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="Roles" minOccurs="0" maxOccurs="1" type="RolesBlockType"/>
<xs:element name="EntrustProfile" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<xs:element name="UserDataApproved" type="myidbase:YesNoOneZero" minOccurs="0" maxOccurs="1"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="RolesBlockType">
<xs:sequence>
<xs:element name="Role" minOccurs="0" maxOccurs="unbounded" type="RoleBlockType"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="RoleBlockType">
<xs:sequence>
<xs:element name="Name" type="myidbase:String255" minOccurs="1"/>
<xs:element name="Scope" type="RoleScope" minOccurs="0" maxOccurs="1"/>
<xs:element name="LogonMechanism" type="RoleLogonMechanism" minOccurs="0" maxOccurs="1"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="PhotoBlockType">
<xs:sequence>
<xs:choice>
<xs:sequence>
<xs:element name="Encoding" type="FileEncoding" maxOccurs="1" minOccurs="1"/>
<xs:element name="Data" type="myidbase:StringBase64" maxOccurs="1" minOccurs="1"/>
<xs:element name="DateTaken" type="xs:dateTime" maxOccurs="1" minOccurs="0"/>
```

```
<xs:element name="Source" type="myidbase:String50" maxOccurs="1" minOccurs="0"/>
</xs:sequence>
<xs:element name="None" type="myidbase:String50" maxOccurs="1" minOccurs="1"/>
</xs:choice>
</xs:sequence>
</xs:complexType>

<xs:simpleType name="FileEncoding">
<xs:restriction base="xs:string">
<xs:enumeration value="jpg"/>
<xs:enumeration value="gif"/>
<xs:enumeration value="png"/>
<xs:enumeration value="bmp"/>
<xs:enumeration value="378"/>
<xs:enumeration value="385"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="RoleScope">
<xs:restriction base="xs:string">
<xs:enumeration value="None"/>
<xs:enumeration value="Self"/>
<xs:enumeration value="Department"/>
<xs:enumeration value="Division"/>
<xs:enumeration value="All"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="RoleLogonMechanism">
<xs:restriction base="xs:string">
<xs:enumeration value="Password"/>
<xs:enumeration value="Card"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="UserAction">
<xs:restriction base="xs:string">
<xs:enumeration value="Disable"/>
<xs:enumeration value="Remove"/>
<xs:enumeration value="CancelDevices"/>
<xs:enumeration value="CancelDevice"/>
<xs:enumeration value="CancelJob"/>
<xs:enumeration value="CancelAllJobs"/>
<xs:enumeration value="UnlockCard"/>
```

```
<xs:enumeration value="RenewCertificate"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="RenewalString">
<xs:restriction base="xs:string">
<xs:enumeration value="true"/>
<xs:enumeration value="false"/>
</xs:restriction>
</xs:simpleType>

<xs:complexType name="JobParameters">
<xs:sequence>
<xs:element name="UnlockPIN" type="xs:unsignedInt" maxOccurs="1" minOccurs="0" />
</xs:sequence>
</xs:complexType>

<xs:complexType name="ActionsBlockType">
<xs:sequence>
<xs:element name="ApplicantAction" type="UserAction" minOccurs="0" maxOccurs="1"/>
<!-- MPS-69 to support certificate renewal -->
<xs:element name="CertSerialNumber" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<xs:element name="CertPolicyName" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<!-- -->
<xs:element name="StatusMappingID" type="xs:unsignedInt" minOccurs="0" maxOccurs="1"/>
<xs:element name="RevocationComment" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="RevocationDelay" type="xs:unsignedInt" minOccurs="0" maxOccurs="1"/>
<xs:element name="Device" minOccurs="0">
<xs:complexType>
<xs:sequence>
<xs:element name="DeviceIdentifier" minOccurs="0" maxOccurs="unbounded" type="DeviceIdentifierBlockType"/>
<xs:element name="ProcessStatus" type="myidbase:String50" minOccurs="0" maxOccurs="1" />
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="RequestedBy" type="myidbase:String255" minOccurs="0" maxOccurs="1" />
<xs:element name="Job" type="xs:unsignedInt" minOccurs="0" maxOccurs="unbounded" />
<xs:element name="Filters" type="FilterCriteria" minOccurs="0" maxOccurs="1" />
</xs:sequence>
</xs:complexType>

<xs:complexType name="DeviceIdentifierBlockType">
```

```
<xs:sequence>
    <xs:element name="SerialNumber" type="myidbase:String50" minOccurs="1"/>
    <xs:element name="SerialNumberField" type="myidbase:String50" minOccurs="0"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="FilterCriteria">
    <xs:sequence>
        <xs:element name="Filter" minOccurs="1" maxOccurs="unbounded">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="FieldName" type="xs:string" minOccurs="0" maxOccurs="1" />
                    <xs:element name="FieldValue" type="xs:string" minOccurs="0" maxOccurs="1" />
                    <xs:element name="Operation" minOccurs="1" maxOccurs="1" type="myidbase:OperationType"/>
                    <xs:element name="Or" type="xs:boolean" minOccurs="0" maxOccurs="1" />
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="GenerateOTPBlockType">
    <xs:sequence>
        <xs:element name="Notification" minOccurs="0" maxOccurs="unbounded">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Name" type="myidbase:String255" minOccurs="1" maxOccurs="1" />
                    <xs:element name="Action" type="myidbase:String10" minOccurs="0" maxOccurs="1" />
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>

</xs:schema>
```

9.4 CMSCardRequest schema

This schema is used for user data sent to the import service to request cards.

```
<?xml version="1.0"?>
<xs:schema
    id="CMSCardRequest"
    targetNamespace="http://www.intercede.com/MyIDSschema/CMSCardRequest"
```

```
xmlns:myidbase="http://www.intercede.com/CommonTypes"
xmlns="http://www.intercede.com/MyIDSchema/CMSCardRequest"
xmlns:xss="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
attributeFormDefault="unqualified" elementFormDefault="qualified"
>
<xs:include schemaLocation="CMSSchemaTypes.xsd" />
<xs:import namespace="http://www.intercede.com/CommonTypes" schemaLocation="MyIDBaseTypes.xsd"/>

<xs:element name="CMSCardRequest" msdata:IsDataSet="true" msdata:Locale="en-GB" msdata:EnforceConstraints="false">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Parameters" minOccurs="0" maxOccurs="1" type="ParametersBlockType"/>
            <xs:element name="Group" minOccurs="0" maxOccurs="1" type="GroupBlockType"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>

<xs:complexType name="GroupBlockType">
    <xs:sequence>
        <xs:element name="Name" type="myidbase:String100" minOccurs="1"/>
        <xs:element name="Description" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
        <xs:element name="OrgUnit" type="myidbase:String1024" minOccurs="0"/>
        <xs:element name="Parent" type="myidbase:String80" minOccurs="0"/>
        <xs:element name="AdditionalFields" minOccurs="0" maxOccurs="1">
            <xs:complexType mixed="true">
                <xs:sequence>
                    <xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="User" minOccurs="0" maxOccurs="1" type="UserBlockType"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="UserBlockType">
    <xs:sequence>
        <xs:element name="Personal" type="PersonalBlockType"/>
        <xs:element name="Authentication" type="AuthenticationBlockType" minOccurs="0" maxOccurs="1" />
        <xs:element name="Card" minOccurs="0" type="CardBlockType"/>
        <xs:element name="CardUpdate" minOccurs="0" type="CardUpdateBlockType"/>
        <xs:element name="Account" minOccurs="0" type="AccountBlockType" />
        <xs:element name="Photo" minOccurs="0" type="PhotoBlockType"/>
        <xs:element name="AdditionalFields" minOccurs="0" maxOccurs="1">
```

```
<xs:complexType mixed="true">
    <xs:sequence>
        <xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Actions" minOccurs="0" maxOccurs="1" type="ActionsBlockType"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="CardBlockType">
    <xs:sequence>
        <xs:element name="CardProfile" type="myidbase:String50" minOccurs="0"/>
        <xs:element name="CardExpiryDate" type="xs:date" minOccurs="0"/>
        <xs:element name="Renewal" type="RenewalString" minOccurs="0"/>
        <xs:element name="CardRequestedBy" type="myidbase:String255" minOccurs="0"/>
        <xs:element name="CancelExisting" minOccurs="0" maxOccurs="1"/>
        <xs:element name="JobLabel" type="myidbase:String50" minOccurs="0"/>
        <xs:element name="Update" minOccurs="0" maxOccurs="1" type="UpdateCardBlockType"/>
        <xs:element name="Replacement" minOccurs="0" type="ReplacementCardBlockType"/>
        <xs:element name="GenerateOTP" minOccurs="0" maxOccurs="1" type="GenerateOTPBlockType"/>
        <xs:element name="OriginalSerialNumber" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
        <xs:element name="OriginalDeviceType" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
        <xs:element name="SerialNumber" type="myidbase:String50" minOccurs="0" maxOccurs="1" />
        <xs:element name="DeviceType" type="myidbase:String50" minOccurs="0" maxOccurs="1" />
        <xs:element name="StatusMapping" type="xs:unsignedByte" minOccurs="0" maxOccurs="1"/>
            <xs:element name="Reprovision" type="xs:unsignedByte" minOccurs="0" maxOccurs="1"/>
            <xs:element name="CardLayout" type="myidbase:String50" minOccurs="0" maxOccurs="1" />
        <xs:element name="AdditionalFields" minOccurs="0" maxOccurs="1">
            <xs:complexType mixed="true">
                <xs:sequence>
                    <xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>
```

</xs:schema>

9.5 CMSUserUpdate schema

This schema is used to update existing users.

```
<?xml version="1.0"?>
<xss:schema
    id="CMSCardRequest"
    targetNamespace="http://www.intercede.com/MyIDSchema/CMSCardRequest"
    xmlns:myidbase="http://www.intercede.com/CommonTypes"
    xmlns="http://www.intercede.com/MyIDSchema/CMSCardRequest"
    xmlns:xss="http://www.w3.org/2001/XMLSchema"
    xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
    attributeFormDefault="unqualified" elementFormDefault="qualified">

    <xss:include schemaLocation="CMSSchemaTypes.xsd" />
    <xss:import namespace="http://www.intercede.com/CommonTypes" schemaLocation="MyIDBaseTypes.xsd"/>

    <xss:element name="CMSCardRequest" msdata:IsDataSet="true" msdata:Locale="en-GB" msdata:EnforceConstraints="false">
        <xss:complexType>
            <xss:sequence>
                <xss:element name="Parameters" minOccurs="0" maxOccurs="1" type="ParametersBlockType"/>
                <xss:element name="Group" maxOccurs="unbounded" minOccurs="0" type="GroupBlockType"/>
                    <xss:element name="User" minOccurs="0" maxOccurs="unbounded" type="UserBlockType"/>
                </xss:sequence>
            </xss:complexType>
        </xss:element>
    </xss:element>

    <xss:complexType name="GroupBlockType">
        <xss:sequence>
            <xss:element name="Name" type="myidbase:String80" minOccurs="1"/>
            <xss:element name="OrgUnit" type="myidbase:String255" minOccurs="0"/>
            <xss:element name="Parent" type="myidbase:String80" minOccurs="0"/>
            <xss:element name="AdditionalGroupFields" minOccurs="0" maxOccurs="1">
                <xss:complexType mixed="true">
                    <xss:sequence>
                        <xss:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
                    </xss:sequence>
                </xss:complexType>
            </xss:element>
            <xss:element name="User" maxOccurs="unbounded" type="UserBlockType"/>
        </xss:sequence>
    </xss:complexType>
</xss:schema>
```

```
<xs:complexType name="UserBlockType">
  <xs:sequence>
    <xs:element name="Personal" type="PersonalBlockType"/>
    <xs:element name="Authentication" minOccurs="0" maxOccurs="1" type="AuthenticationBlockType"/>
    <xs:element name="Card" minOccurs="0" type="CardBlockType"/>
    <xs:element name="Account" minOccurs="0" type="AccountBlockType" />
    <xs:element name="Photo" minOccurs="0" type="PhotoBlockType"/>
    <xs:element name="AdditionalFields" minOccurs="0" maxOccurs="1">
      <xs:complexType mixed="true">
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Actions" minOccurs="0" maxOccurs="1" type="ActionsBlockType"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="CardBlockType">
  <xs:sequence>
    <xs:element name="CardProfile" type="myidbase:String50" minOccurs="0"/>
    <xs:element name="CardExpiryDate" type="xs:date" minOccurs="0"/>
    <xs:element name="CardRequestedBy" type="myidbase:String255" minOccurs="0"/>
    <xs:element name="Update" minOccurs="0" maxOccurs="1" type="UpdateCardBlockType"/>
      <xs:element name="Reprovision" type="xs:unsignedByte" minOccurs="0" maxOccurs="1"/>
    </xs:sequence>
  </xs:complexType>
</xs:complexType>

</xs:schema>
```

9.6 CMSImportResponse schema

This schema is used by the import service to pass back information about the user import.

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="CMSImportResponse" targetNamespace="http://www.intercede.com/MyIDSschema/CMSImportResponse"
  xmlns:mstns="http://www.intercede.com/MyIDSschema/CMSImportResponse" attributeFormDefault="unqualified"
  elementFormDefault="qualified" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="CMSImportResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="Group" minOccurs="0" maxOccurs="unbounded">
          <xs:complexType>
```

```
<xs:sequence>
    <xs:element name="Name" type="mstns:String80" minOccurs="1" maxOccurs="1"/>
    <xs:element name="Result" type="mstns:ActionStatus" minOccurs="1" maxOccurs="1" />
    <xs:element name="User" type="mstns:User" minOccurs="0" maxOccurs="unbounded" />
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="User" type="mstns:User" minOccurs="0" maxOccurs="unbounded" />
</xs:sequence>
</xs:complexType>
</xs:element>

<xs:complexType name="User">
    <xs:sequence>
        <xs:element name="FirstName" type="mstns:String64" minOccurs="1" maxOccurs="1"/>
        <xs:element name="LastName" type="mstns:String64" minOccurs="1" maxOccurs="1"/>
        <xs:element name="EmployeeID" type="mstns:String50" minOccurs="1" maxOccurs="1"/>
        <xs:element name="LogonName" type="mstns:String50" minOccurs="1" maxOccurs="1"/>
        <xs:element name="CardRequest" type="xs:int" minOccurs="1" maxOccurs="1" />
        <xs:element name="UnlockCardRequest" type="xs:int" minOccurs="1" maxOccurs="1" />
        <xs:element name="Result" type="mstns:ActionStatus" minOccurs="1" maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>

<xs:simpleType name="String50">
    <xs:restriction base="xs:string">
        <xs:maxLength value="50" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String80">
    <xs:restriction base="xs:string">
        <xs:maxLength value="80" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String64">
    <xs:restriction base="xs:string">
        <xs:maxLength value="64" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ActionStatus">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Added"/>
        <xs:enumeration value="Created"/>
    </xs:restriction>
</xs:simpleType>
```

```
<xs:enumeration value="Already Exists"/>
<xs:enumeration value="Failed"/>
    <xs:enumeration value="Removed"/>
    <xs:enumeration value="License Limit"/>
</xs:restriction>
</xs:simpleType>
</xs:schema>
```

9.7 PIVSchemaTypes

```
<?xml version="1.0"?>
<xs:schema
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    xmlns:myidbase="http://www.intercede.com/CommonTypes"
    targetNamespace="http://www.intercede.com/MyIDPIVSchema/PivCardRequest"
    xmlns="http://www.intercede.com/MyIDPIVSchema/PivCardRequest"
    elementFormDefault="qualified" attributeFormDefault="qualified"
>
    <xs:import namespace="http://www.intercede.com/CommonTypes" schemaLocation="MyIDBaseTypes.xsd"/>

    <xs:complexType name="ParametersBlockType">
        <xs:all>
            <xs:element name="SourceID" type="xs:string" minOccurs="1" maxOccurs="1"/>
            <xs:element name="IssueDate" type="xs:date" minOccurs="0" maxOccurs="1"/>
            <xs:element name="GenerateUserDN" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
            <xs:element name="ActionOnDuplicate" type="xs:string" minOccurs="1" maxOccurs="1"/>
            <xs:element name="RolesActionOnDuplicate" type="xs:string" minOccurs="1" maxOccurs="1"/>
            <xs:element name="DeleteMissingUsers" type="xs:unsignedInt" minOccurs="1" maxOccurs="1"/>
            <xs:element name="PushToLDAP" type="xs:unsignedInt" minOccurs="1" maxOccurs="1"/>
            <xs:element name="CreateUnknownGroups" type="xs:unsignedInt" minOccurs="1" maxOccurs="1"/>
            <xs:element name="AuditAll" type="myidbase:Int1" minOccurs="1" maxOccurs="1"/>
            <xs:element name="DataType" type="xs:string" minOccurs="0" maxOccurs="1"/>
            <xs:element name="CheckImportResponseSchema" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
            <xs:element name="SynchronousImport" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
            <xs:element name="AllowBioImport" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
            <xs:element name="DefaultUserRole" type="xs:string" minOccurs="0" maxOccurs="1"/>
            <xs:element name="DisallowCertificateSuspension" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
            <xs:element name="CardRequestThrottling" type="xs:unsignedInt" minOccurs="0" maxOccurs="1"/>
            <xs:element name="ReplaceUnassignedCards" type="myidbase:Int1" minOccurs="0" maxOccurs="1"/>
        </xs:all>
    </xs:complexType>
```

```
<xs:complexType name="AgencyAddressBlockType">
  <xs:sequence>
    <xs:element name="Address1" type="myidbase:String40" minOccurs="0"/>
    <xs:element name="Address2" type="myidbase:String40" minOccurs="0"/>
    <xs:element name="City" type="myidbase:String40" minOccurs="1"/>
    <xs:element name="State" type="myidbase:String40" minOccurs="0"/>
    <xs:element name="Zip" type="myidbase:String10" minOccurs="0"/>
    <xs:element name="PhoneNumber" type="myidbase:String30" minOccurs="0"/>
    <xs:element name="Country" type="myidbase:String40" minOccurs="0"/>
    <xs:element name="Email" type="myidbase:String120" minOccurs="0"/>
    <xs:element name="Contact" type="myidbase:String80" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<!-- Complex PIV elements -->
<xs:complexType name="PersonalBlockType">
  <xs:sequence>
    <xs:element name="FirstName" type="myidbase:NotEmptyString64" minOccurs="1"/>
    <xs:element name="LastName" type="myidbase:NotEmptyString64" minOccurs="1"/>
    <xs:element name="NickName" type="myidbase:String80" minOccurs="0"/>
    <xs:element name="MiddleName" type="myidbase:String10" minOccurs="0"/>
    <xs:element name="Suffix" type="myidbase:String20" minOccurs="0"/>
    <xs:element name="Title" type="myidbase:String20" minOccurs="0"/>
    <xs:element name="Email" type="myidbase:String255" minOccurs="0"/>
    <xs:element name="Fax" type="myidbase:String50" minOccurs="0"/>
    <xs:element name="Cell" type="myidbase:String50" minOccurs="0"/>
    <xs:element name="Phone" type="myidbase:String50" minOccurs="0"/>
    <xs:element name="EmployeeID" type="myidbase:Int50" minOccurs="1"/>
    <xs:element name="Address" minOccurs="0" type="PersonalAddressBlockType" />
    <xs:element name="BirthDate" type="xs:date" minOccurs="0"/>
    <xs:element name="Nationality" type="myidbase:String4" minOccurs="0"/>
    <xs:element name="Citizenship" type="CitizenshipString" minOccurs="0"/>
      <xs:element name="CountryOfBirth" type="myidbase:String2" minOccurs="0"/>
    <xs:element name="PlaceOfBirth" type="myidbase:String2" minOccurs="0"/>
    <xs:element name="ExportRestrictions" type="ExportRestrictionsString" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="CardBlockType">
  <xs:sequence>
    <xs:element name="CardProfile" type="myidbase:String50" minOccurs="0"/>
    <xs:element name="CardExpiryDate" type="xs:date" minOccurs="0"/>
    <xs:element name="Renewal" type="RenewalString" minOccurs="0"/>
    <xs:element name="CardRequestedBy" type="myidbase:String255" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
```

```
<xs:element name="JobLabel" type="myidbase:String50" minOccurs="0"/>
<xs:element name="Update" type="UpdateCardBlockType" minOccurs="0" maxOccurs="1"/>
    <xs:element name="Replacement" type="ReplacementCardBlockType" minOccurs="0"/>
    <xs:element name="Reprovision" type="xs:unsignedByte" minOccurs="0" maxOccurs="1"/>
    <xs:element name="CardLayout" type="myidbase:String50" minOccurs="0" maxOccurs="1" />
    <xs:element name="SerialNumber" type="myidbase:String50" minOccurs="0" maxOccurs="1" />
    <xs:element name="DeviceType" type="myidbase:String50" minOccurs="0" maxOccurs="1" />
</xs:sequence>
</xs:complexType>

<xs:complexType name="UpdateCardBlockType">
    <xs:sequence>
        <xs:element name="OriginalSerialNumber" type="myidbase:String50" minOccurs="1" maxOccurs="1" />
        <xs:element name="OriginalDeviceType" type="myidbase:String50" minOccurs="1" maxOccurs="1" />
        <xs:element name="StatusMapping" type="xs:int" minOccurs="0" maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="ReplacementCardBlockType">
    <xs:all>
        <xs:element name="OriginalSerialNumber" type="myidbase:String50" minOccurs="1" maxOccurs="1"/>
        <xs:element name="OriginalDeviceType" type="myidbase:String50" minOccurs="1" maxOccurs="1"/>
        <xs:element name="StatusMapping" type="xs:int" minOccurs="0" maxOccurs="1"/>
    </xs:all>
</xs:complexType>

<xs:complexType name="PersonalAddressBlockType">
    <xs:sequence>
        <xs:element name="Address1" type="myidbase:String50" minOccurs="0"/>
        <xs:element name="Address2" type="myidbase:String50" minOccurs="0"/>
        <xs:element name="City" type="myidbase:String50" minOccurs="0"/>
        <xs:element name="StateZip" type="myidbase:String50" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="AuthenticationBlockType">
    <xs:sequence>
        <xs:element name="SecurityPhrase" minOccurs="0" maxOccurs="unbounded" >
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="Prompt" type="myidbase:NotEmptyString255" minOccurs="1" maxOccurs="1"/>
                    <xs:element name="Answer" type="myidbase:EncryptedData" minOccurs="1" maxOccurs="1"/>
                </xs:sequence>
            </xs:complexType>
        </xs:sequence>
    </xs:complexType>
```

```
</xs:element>
</xs:sequence>
</xs:complexType>

<xs:complexType name="AccountBlockType">
  <xs:sequence>
    <xs:element name="DN" type="myidbase:String1024" minOccurs="0"/>
    <xs:element name="AlternateDN" type="myidbase:String1024" minOccurs="0"/>
    <xs:element name="CN" type="myidbase:String255" minOccurs="0"/>
    <xs:element name="OU" type="myidbase:String1024" minOccurs="0"/>
    <xs:element name="UPN" type="myidbase:String255" minOccurs="0"/>
    <xs:element name="SAMAccountName" type="myidbase:String20" minOccurs="0"/>
    <xs:element name="Domain" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
    <xs:element name="LogonName" type="myidbase:String255" minOccurs="0"/>
    <xs:element name="Roles" minOccurs="0" maxOccurs="1" type="RolesBlockType"/>
    <xs:element name="EntrustProfile" type="myidbase:String50" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="RolesBlockType">
  <xs:sequence>
    <xs:element name="Role" minOccurs="0" maxOccurs="unbounded">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Name" type="myidbase:String255" minOccurs="1"/>
          <xs:element name="Scope" type="RoleScope" minOccurs="0" maxOccurs="1"/>
          <xs:element name="LogonMechanism" type="RoleLogonMechanism" minOccurs="0" maxOccurs="1"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="PositionBlockType">
  <xs:sequence>
    <xs:element name="EmployeeAssociation" type="Association" minOccurs="0"/>
    <xs:element name="EmployeeAffiliation" type="myidbase:String64" minOccurs="0"/>
    <xs:element name="Rank" type="Rank" minOccurs="0"/>
    <xs:element name="EmergencyRole" type="EmergencyRole" minOccurs="0"/>
    <xs:element name="Privilege" type="myidbase:String50" minOccurs="0"/>
    <xs:element name="ApplicantPosition" type="myidbase:String30" minOccurs="0"/>
    <xs:element name="ExtraInfo" type="myidbase:String80" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
```

```
<xs:complexType name="BiometryBlockType">
  <xs:sequence>
    <xs:element name="HeightInches" type="myidbase:String8" minOccurs="0"/>
    <xs:element name="WeightLbs" type="myidbase:String8" minOccurs="0"/>
    <xs:element name="Gender" type="Gender" minOccurs="0"/>
    <xs:element name="EyeColor" type="EyeColor" minOccurs="0"/>
    <xs:element name="HairColor" type="HairColor" minOccurs="0"/>
    <xs:element name="Race" type="Race" minOccurs="0"/>
    <xs:element name="BioSample" minOccurs="0" type="BioSampleBlockType"/>
    <xs:element name="Signature" minOccurs="0">
      <xs:complexType>
        <xs:group ref="EncodedData"/>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="BioSampleBlockType">
  <xs:all>
    <xs:element name="R_Little" minOccurs="0">
      <xs:complexType>
        <xs:group ref="BioFingerSample"/>
      </xs:complexType>
    </xs:element>
    <xs:element name="R_Ring" minOccurs="0">
      <xs:complexType>
        <xs:group ref="BioFingerSample"/>
      </xs:complexType>
    </xs:element>
    <xs:element name="R_Middle" minOccurs="0">
      <xs:complexType>
        <xs:group ref="BioFingerSample"/>
      </xs:complexType>
    </xs:element>
    <xs:element name="R_Index" minOccurs="0">
      <xs:complexType>
        <xs:group ref="BioFingerSample"/>
      </xs:complexType>
    </xs:element>
    <xs:element name="R_Thumb" minOccurs="0">
      <xs:complexType>
        <xs:group ref="BioFingerSample"/>
      </xs:complexType>
    </xs:element>
```

```
</xs:element>
<xs:element name="L_Little" minOccurs="0">
  <xs:complexType>
    <xs:group ref="BioFingerSample"/>
  </xs:complexType>
</xs:element>
<xs:element name="L_Ring" minOccurs="0">
  <xs:complexType>
    <xs:group ref="BioFingerSample"/>
  </xs:complexType>
</xs:element>
<xs:element name="L_Middle" minOccurs="0">
  <xs:complexType>
    <xs:group ref="BioFingerSample"/>
  </xs:complexType>
</xs:element>
<xs:element name="L_Index" minOccurs="0">
  <xs:complexType>
    <xs:group ref="BioFingerSample"/>
  </xs:complexType>
</xs:element>
<xs:element name="L_Thumb" minOccurs="0">
  <xs:complexType>
    <xs:group ref="BioFingerSample"/>
  </xs:complexType>
</xs:element>
<xs:element name="EFT" minOccurs="0">
  <xs:complexType>
    <xs:group ref="EncodedData"/>
  </xs:complexType>
</xs:element>
<xs:element name="FaceScan" minOccurs="0">
  <xs:complexType>
    <xs:group ref="EncodedData"/>
  </xs:complexType>
</xs:element>
<xs:element name="IrisScan" minOccurs="0">
  <xs:complexType>
    <xs:group ref="EncodedData"/>
  </xs:complexType>
</xs:element>
</xs:all>
</xs:complexType>
```

```
<xs:group name="BioFingerSample">
  <xs:sequence>
    <xs:choice>
      <xs:sequence>
        <xs:group ref="EncodedData"/>
        <xs:element name="RolledPrint" type="myidbase:YesNo" maxOccurs="1" minOccurs="0"/>
      </xs:sequence>
      <xs:element name="ReasonMissing" type="MissingFingerReason" minOccurs="0" maxOccurs="1"/>
    </xs:choice>
  </xs:sequence>
</xs:group>

<xs:group name="EncodedData">
  <xs:sequence>
    <xs:element name="Encoding" type="FileEncoding" maxOccurs="1" minOccurs="1"/>
    <xs:element name="Data" type="myidbase:StringBase64" maxOccurs="1" minOccurs="1"/>
    <xs:element name="DateTaken" type="xs:dateTime" maxOccurs="1" minOccurs="0"/>
    <xs:element name="Source" type="myidbase:String50" maxOccurs="1" minOccurs="0"/>
  </xs:sequence>
</xs:group>

<xs:complexType name="IdentityDocumentsBlockType">
  <xs:sequence>
    <xs:element name="IdentityDoc1" minOccurs="0">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Image">
            <xs:complexType>
              <xs:group ref="EncodedData"/>
            </xs:complexType>
          </xs:element>
          <xs:element name="Title" type="IDDocName1"/>
          <xs:element name="IssuedBy" type="myidbase:String80"/>
          <xs:element name="Number" type="myidbase:String20"/>
          <xs:element name="Expiry" type="xs:date"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="IdentityDoc2" minOccurs="0">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="Image">
            <xs:complexType>
              <xs:group ref="EncodedData"/>
            </xs:complexType>
          </xs:element>
```

```
</xs:complexType>
</xs:element>
<xs:element name="Title" type="IDDocName2"/>
<xs:element name="IssuedBy" type="myidbase:String80"/>
<xs:element name="Number" type="myidbase:String20"/>
<xs:element name="Expiry" type="xs:date"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="SPF10" minOccurs="0">
<xs:complexType>
<xs:sequence>
<xs:element name="Image">
<xs:complexType>
<xs:group ref="EncodedData"/>
</xs:complexType>
</xs:element>
<xs:element name="Title"/>
<xs:element name="IssuedBy"/>
<xs:element name="Number"/>
<xs:element name="Expiry"/>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
<xs:simpleType name="IDDocName1">
<xs:restriction base="xs:string">
<!-- the following items are allowable under FIPS201-2 -->
<xs:enumeration value="U.S. Passport"/>
<xs:enumeration value="Foreign Passport"/>
<xs:enumeration value="Alien Regn Receipt Card"/>
<xs:enumeration value="Employment Authorization"/>
<xs:enumeration value="Drivers License"/>
<xs:enumeration value="U.S. Military Card"/>
<xs:enumeration value="U.S. Military dependent ID Card"/>
<xs:enumeration value="PIV Card"/>
<!-- the following items are legacy items which need to be retained to support existing functionality -->
<xs:enumeration value="Cert. of U.S. Citizenship"/>
<xs:enumeration value="Cert. of Naturalization"/>
<xs:enumeration value="Temporary Card"/>
<xs:enumeration value="Reentry Permit"/>
<xs:enumeration value="Refugee Travel Document"/>
```

```
<xs:enumeration value="Photo ID Card"/>
<xs:enumeration value="School ID Card"/>
<xs:enumeration value="Voters Regn Card"/>
<xs:enumeration value="Merchant Mariner Card"/>
<xs:enumeration value="Native American Tribal"/>
<xs:enumeration value="Canadian Drivers License"/>
<xs:enumeration value="School Report"/>
<xs:enumeration value="Hospital Record"/>
<xs:enumeration value="Nursery Record"/>
<xs:enumeration value="U.S. Social Security"/>
<xs:enumeration value="Cert. of Birth Abroad"/>
<xs:enumeration value="Birth Certificate"/>
<xs:enumeration value="U.S. Citizen ID"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="IDDocName2">
<xs:restriction base="xs:string">
    <!-- the following items are allowable under FIPS201-2 -->
    <xs:enumeration value="U.S. Passport"/>
    <xs:enumeration value="Cert. of U.S. Citizenship"/>
    <xs:enumeration value="Cert. of Naturalization"/>
    <xs:enumeration value="Foreign Passport"/>
    <xs:enumeration value="Alien Regn Receipt Card"/>
    <xs:enumeration value="Temporary Card"/>
    <xs:enumeration value="Reentry Permit"/>
    <xs:enumeration value="Refugee Travel Document"/>
    <xs:enumeration value="Employment Authorization"/>
    <xs:enumeration value="Drivers License"/>
    <xs:enumeration value="Photo ID Card"/>
    <xs:enumeration value="Voters Regn Card"/>
    <xs:enumeration value="U.S. Military Card"/>
    <xs:enumeration value="Merchant Mariner Card"/>
    <xs:enumeration value="Native American Tribal"/>
    <xs:enumeration value="Canadian Drivers License"/>
    <xs:enumeration value="U.S. Social Security"/>
    <xs:enumeration value="Cert. of Birth Abroad"/>
    <xs:enumeration value="Birth Certificate"/>
    <xs:enumeration value="U.S. Citizen ID"/>
    <xs:enumeration value="U.S. Resident Citizen Card (I-179)"/>
    <xs:enumeration value="Employment Auth Card (I-688A)"/>
    <xs:enumeration value="Employment Auth Doc (DHS)"/>
    <xs:enumeration value="Employment Auth Doc (I-688B)"/>
    <!-- the following items are legacy items which need to be retained to support existing functionality -->
```

```
<xs:enumeration value="School ID Card"/>
<xs:enumeration value="School Report"/>
<xs:enumeration value="Hospital Record"/>
<xs:enumeration value="Nursery Record"/>
</xs:restriction>
</xs:simpleType>

<xs:complexType name="NACIStatusBlockType">
<xs:sequence>
<xs:element name="NACCCaseNumber" type="xs:unsignedShort" minOccurs="0"/>
<xs:element name="NACICaseNumber" type="xs:unsignedShort" minOccurs="0"/>
<xs:element maxOccurs="unbounded" name="Check">
<xs:complexType>
<xs:sequence>
<xs:element name="Type" type="myidbase:String20"/>
<xs:element name="Status" type="NACState"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CardIssuanceApproved" type="myidbase:YesNoOneZero" minOccurs="0"/>
<xs:element name="Comments" type="myidbase:String255" minOccurs="0"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="ActionsBlockType">
<xs:sequence>
<xs:element name="ApplicantAction" type="UserAction" minOccurs="0" maxOccurs="1"/>
<xs:element name="CertSerialNumber" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<xs:element name="CertPolicyName" type="myidbase:String50" minOccurs="0" maxOccurs="1"/>
<xs:element name="StatusMappingID" type="xs:unsignedInt" minOccurs="0" maxOccurs="1"/>
<xs:element name="RevocationComment" type="myidbase:String255" minOccurs="0" maxOccurs="1"/>
<xs:element name="Device" minOccurs="0">
<xs:complexType>
<xs:sequence>
<xs:element name="DeviceIdentifier" minOccurs="0" maxOccurs="unbounded" type="DeviceIdentifierBlockType"/>
<xs:element name="ProcessStatus" type="myidbase:String50" minOccurs="0" maxOccurs="1" />
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Job" type="xs:unsignedInt" minOccurs="0" maxOccurs="unbounded" />
</xs:sequence>
</xs:complexType>

<xs:complexType name="DeviceIdentifierBlockType">
```

```
<xs:sequence>
  <xs:element name="SerialNumber" type="myidbase:String50" minOccurs="1"/>
  <xs:element name="SerialNumberField" type="myidbase:String50" minOccurs="0"/>
</xs:sequence>
</xs:complexType>

<!-- simple/base PIV types -->
<xs:simpleType name="RenewalString">
  <xs:restriction base="xs:string">
    <xs:enumeration value="true"/>
    <xs:enumeration value="false"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="CitizenshipString">
  <xs:restriction base="xs:string">
    <xs:enumeration value="US"/>
    <xs:enumeration value="Non US"/>
    <xs:enumeration value="PR"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ExportRestrictionsString">
  <xs:restriction base="xs:string">
    <xs:enumeration value="EXP"/>
    <xs:enumeration value="" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="RoleScope">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Self"/>
    <xs:enumeration value="Department"/>
    <xs:enumeration value="Division"/>
    <xs:enumeration value="All"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="RoleLogonMechanism">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Password"/>
    <xs:enumeration value="Card"/>
  </xs:restriction>
```

```
</xs:simpleType>

<xs:simpleType name="Association">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Employee"/>
    <xs:enumeration value="Civil Worker"/>
    <xs:enumeration value="Executive"/>
    <xs:enumeration value="Uniformed"/>
    <xs:enumeration value="Contractor"/>
    <xs:enumeration value="Affiliate"/>
    <xs:enumeration value="Beneficiary"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="Rank">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Civilian"/>
    <xs:enumeration value="E-1"/>
    <xs:enumeration value="E-2"/>
    <xs:enumeration value="E-3"/>
    <xs:enumeration value="E-4"/>
    <xs:enumeration value="E-5"/>
    <xs:enumeration value="E-6"/>
    <xs:enumeration value="E-7"/>
    <xs:enumeration value="E-8"/>
    <xs:enumeration value="E-9"/>
    <xs:enumeration value="ES-1"/>
    <xs:enumeration value="ES-2"/>
    <xs:enumeration value="ES-3"/>
    <xs:enumeration value="ES-4"/>
    <xs:enumeration value="ES-5"/>
    <xs:enumeration value="ES-6"/>
    <xs:enumeration value="GS-1"/>
    <xs:enumeration value="GS-10"/>
    <xs:enumeration value="GS-11"/>
    <xs:enumeration value="GS-12"/>
    <xs:enumeration value="GS-13"/>
    <xs:enumeration value="GS-14"/>
    <xs:enumeration value="GS-15"/>
    <xs:enumeration value="GS-1"/>
    <xs:enumeration value="GS-2"/>
    <xs:enumeration value="GS-3"/>
    <xs:enumeration value="GS-4"/>
    <xs:enumeration value="GS-5"/>
```

```
<xs:enumeration value="GS-6"/>
<xs:enumeration value="GS-7"/>
<xs:enumeration value="GS-8"/>
<xs:enumeration value="GS-9"/>
<xs:enumeration value="O-10"/>
<xs:enumeration value="O-11"/>
<xs:enumeration value="O-1"/>
<xs:enumeration value="O-2"/>
<xs:enumeration value="O-3"/>
<xs:enumeration value="O-4"/>
<xs:enumeration value="O-5"/>
<xs:enumeration value="O-6"/>
<xs:enumeration value="O-7"/>
<xs:enumeration value="O-8"/>
<xs:enumeration value="O-9"/>
<xs:enumeration value="W-1"/>
<xs:enumeration value="W-2"/>
<xs:enumeration value="W-3"/>
<xs:enumeration value="W-4"/>
<xs:enumeration value="W-5"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="EmergencyRole">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Law Enforcement"/>
    <xs:enumeration value="Paramedic"/>
    <xs:enumeration value="Doctor"/>
    <xs:enumeration value="Firefighter"/>
    <xs:enumeration value="Bomb Disposal"/>
    <xs:enumeration value="Biohazard"/>
    <xs:enumeration value="None"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="Gender">
  <xs:restriction base="xs:string">
    <xs:enumeration value="F"/>
    <xs:enumeration value="M"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="EyeColor">
  <xs:restriction base="xs:string">
```

```
<xs:enumeration value="BLK"/>
<xs:enumeration value="BLU"/>
<xs:enumeration value="BRO"/>
<xs:enumeration value="GRY"/>
<xs:enumeration value="GRN"/>
<xs:enumeration value="HAZ"/>
<xs:enumeration value="MAR"/>
<xs:enumeration value="PNK"/>
<xs:enumeration value="XXX"/>
<xs:enumeration value="MUL"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="HairColor">
  <xs:restriction base="xs:string">
    <xs:enumeration value="XXX"/>
    <xs:enumeration value="BAL"/>
    <xs:enumeration value="BLK"/>
    <xs:enumeration value="BLN"/>
    <xs:enumeration value="BLU"/>
    <xs:enumeration value="BRO"/>
    <xs:enumeration value="GRY"/>
    <xs:enumeration value="GRN"/>
    <xs:enumeration value="ONG"/>
    <xs:enumeration value="PNK"/>
    <xs:enumeration value="PLE"/>
    <xs:enumeration value="RED"/>
    <xs:enumeration value="SDY"/>
    <xs:enumeration value="STR"/>
    <xs:enumeration value="WHI"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="Race">
  <xs:restriction base="xs:string">
    <xs:enumeration value="A"/>
    <xs:enumeration value="B"/>
    <xs:enumeration value="I"/>
    <xs:enumeration value="W"/>
    <xs:enumeration value="O"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="MissingFingerReason">
```

```
<xs:restriction base="xs:string">
  <xs:enumeration value="Unprintable"/>
  <xs:enumeration value="Amputated"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="NACState">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NR"/>
    <xs:enumeration value="WR"/>
    <xs:enumeration value="AS"/>
    <xs:enumeration value="AP"/>
    <xs:enumeration value="RJ"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="UserAction">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Disable"/>
    <xs:enumeration value="Remove"/>
    <xs:enumeration value="CancelDevices"/>
    <xs:enumeration value="CancelDevice"/>
    <xs:enumeration value="CancelJob"/>
    <xs:enumeration value="CancelAllJobs"/>
    <xs:enumeration value="RenewCertificate"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="FileEncoding">
  <xs:restriction base="xs:string">
    <xs:enumeration value="jpg"/>
    <xs:enumeration value="gif"/>
    <xs:enumeration value="png"/>
    <xs:enumeration value="bmp"/>
    <xs:enumeration value="378"/>
    <xs:enumeration value="385"/>
    <xs:enumeration value="19794"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ApplicantStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Sponsored"/>
    <xs:enumeration value="EnrollmentBegun"/>
```

```
<xs:enumeration value="EnrollmentComplete"/>
<xs:enumeration value="Vetting"/>
<xs:enumeration value="Escalated"/>
<xs:enumeration value="Approved"/>
<xs:enumeration value="CardRequested"/>
<xs:enumeration value="CardActivated"/>
<xs:enumeration value="Rejected"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="AgencyCategory">
<xs:restriction base="xs:string">
<xs:enumeration value="Federal"/>
<xs:enumeration value="State"/>
<xs:enumeration value="Commercial"/>
<xs:enumeration value="Foreign"/>
</xs:restriction>
</xs:simpleType>

<xs:simpleType name="AgencyType">
<xs:restriction base="xs:string">
<xs:enumeration value="Agency"/>
<xs:enumeration value="State"/>
<xs:enumeration value="Company"/>
<xs:enumeration value="Country"/>
</xs:restriction>
</xs:simpleType>

</xs:schema>
```

9.8 PivCardRequest

```
<?xml version="1.0"?>
<xs:schema
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    xmlns:myidbase="http://www.intercede.com/CommonTypes"
    targetNamespace="http://www.intercede.com/MyIDPIVSchema/PivCardRequest"
    xmlns="http://www.intercede.com/MyIDPIVSchema/PivCardRequest"
    id="PivCardRequest"
    xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
    elementFormDefault="qualified" attributeFormDefault="qualified">
    <xs:include schemaLocation="PIVSchemaTypes.xsd" />
    <xs:import namespace="http://www.intercede.com/CommonTypes" schemaLocation="MyIDBaseTypes.xsd"/>
```

```
<xs:element name="PivCardRequest" msdata:IsDataSet="true" msdata:Locale="en-GB" msdata:EnforceConstraints="false">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Parameters" minOccurs="0" maxOccurs="1" type="ParametersBlockType"/>
                <xs:element name="Agency" minOccurs="0" maxOccurs="1" type="AgencyBlockType"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>

<xs:complexType name="AgencyBlockType">
    <xs:sequence>
        <xs:element name="DeptCode" type="myidbase:String6" minOccurs="1"/>
        <xs:element name="AgencyCode" type="myidbase:String4" minOccurs="1"/>
        <xs:element name="FacilityCode" type="myidbase:String4" minOccurs="1"/>
        <xs:element name="AgencyName" type="myidbase:String80" minOccurs="1"/>
        <xs:element name="FacilityName" type="myidbase:String80" minOccurs="0"/>
        <xs:element name="DUNS" type="myidbase:Int9" minOccurs="1"/>
        <xs:element name="OC" type="myidbase:Int1" minOccurs="1"/>
        <xs:element name="OI" type="myidbase:Int4" minOccurs="1"/>
        <xs:element name="Department" type="myidbase:String64" minOccurs="0"/>
        <xs:element name="BaseDN" type="myidbase:String1024" minOccurs="0"/>
        <xs:element name="Parent" type="myidbase:String80" minOccurs="0"/>
        <xs:element name="AgencyAddress" minOccurs="0" maxOccurs="1" type="AgencyAddressBlockType"/>
        <xs:element name="AdditionalAgencyFields" minOccurs="0" maxOccurs="1">
            <xs:complexType mixed="true">
                <xs:sequence>
                    <xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
        <xs:element name="Applicant" minOccurs="0" maxOccurs="1" type="ApplicantBlockType"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="ApplicantBlockType">
    <xs:sequence>
        <xs:element name="Personal" type="PersonalBlockType"/>
        <xs:element name="Authentication" type="AuthenticationBlockType" minOccurs="0" maxOccurs="1" />
        <xs:element name="Card" minOccurs="0" maxOccurs="1" type="CardBlockType"/>
        <xs:element name="Account" minOccurs="0" type="AccountBlockType"/>
        <xs:element name="Position" minOccurs="0" type="PositionBlockType"/>
        <xs:element name="Sponsor" minOccurs="1" maxOccurs="1" type="SponsorBlockType"/>
        <xs:element name="Biometry" minOccurs="0" type="BiometryBlockType"/>
    </xs:sequence>
</xs:complexType>
```

```
<xs:element name="IdentityDocs" minOccurs="0" type="IdentityDocumentsBlockType"/>
<xs:element name="NACI" minOccurs="0" type="NACIStatusBlockType"/>
<xs:element name="Photo" minOccurs="0">
  <xs:complexType>
    <xs:group ref="EncodedData"/>
  </xs:complexType>
</xs:element>
<xs:element name="System" minOccurs="0" maxOccurs="1" type="SystemBlockType"/>
<xs:element name="AdditionalFields" minOccurs="0" maxOccurs="1">
  <xs:complexType mixed="true">
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="Actions" minOccurs="0" maxOccurs="1" type="ActionsBlockType"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="SponsorBlockType">
  <xs:sequence>
    <xs:element name="SponsorName" type="myidbase:String80" minOccurs="1" maxOccurs="1"/>
    <xs:element name="SponsorPosition" type="myidbase:String30" minOccurs="0" maxOccurs="1"/>
    <xs:element name="SponsorAgency" type="myidbase:String80" minOccurs="1" maxOccurs="1"/>
    <xs:element name="SponsorEmail" type="myidbase:String120" minOccurs="0" maxOccurs="1"/>
    <xs:element name="SponsorPhoneNumber" type="myidbase:String30" minOccurs="0" maxOccurs="1"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="SystemBlockType">
  <xs:sequence>
    <xs:element name="GUID" type="myidbase:String50" minOccurs="1"/>
    <xs:element name="CredNo" type="myidbase:String8" minOccurs="1"/>
    <xs:element name="CS" type="xs:unsignedInt" minOccurs="0"/>
    <xs:element name="POA" type="xs:unsignedInt" minOccurs="0"/>
    <xs:element name="ICI" type="xs:unsignedInt" minOccurs="1"/>
    <xs:element name="UserStatus" type="myidbase:String50" minOccurs="0"/>
    <xs:element name="IssuanceNotifyURL" type="myidbase:String255" minOccurs="0"/>
    <xs:element name="CancelNotifyURL" type="myidbase:String255" minOccurs="0"/>
    <xs:element name="CMSIssuanceNotifyURL" type="myidbase:String255" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

</xs:schema>
```

9.9 PivApplicantUpdate

```
<?xml version="1.0"?>
<xs:schema
    xmlns:xs="http://www.w3.org/2001/XMLSchema"
    xmlns:myidbase="http://www.intercede.com/CommonTypes"
    targetNamespace="http://www.intercede.com/MyIDPIVSchema/PivCardRequest"
    xmlns="http://www.intercede.com/MyIDPIVSchema/PivCardRequest"
    id="PivApplicantUpdate"
    xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
    elementFormDefault="qualified" attributeFormDefault="qualified"
>
    <xs:include schemaLocation="PIVSchemasTypes.xsd" />
    <xs:import namespace="http://www.intercede.com/CommonTypes" schemaLocation="MyIDBaseTypes.xsd"/>

    <xs:element name="PivCardRequest" msdata:IsDataSet="true" msdata:Locale="en-GB" msdata:EnforceConstraints="false">
        <xs:complexType>
            <xs:sequence>
                <xs:element name="Parameters" minOccurs="0" maxOccurs="1" type="ParametersBlockType"/>
                <xs:element name="Agency" minOccurs="0" maxOccurs="unbounded" type="AgencyBlockType"/>
                    <xs:element name="Applicant" minOccurs="0" maxOccurs="unbounded" type="ApplicantBlockType"/>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:complexType name="AgencyBlockType">
        <xs:sequence>
            <xs:element name="DeptCode" type="myidbase:String6" minOccurs="1"/>
            <xs:element name="AgencyCode" type="myidbase:String4" minOccurs="1"/>
            <xs:element name="FacilityCode" type="myidbase:String4" minOccurs="1"/>
            <xs:element name="AgencyName" type="myidbase:String80" minOccurs="1"/>
            <xs:element name="FacilityName" type="myidbase:String80" minOccurs="0"/>
            <xs:element name="DUNS" type="myidbase:Int9" minOccurs="1"/>
            <xs:element name="OC" type="myidbase:Int1" minOccurs="1"/>
            <xs:element name="OI" type="myidbase:Int4" minOccurs="1"/>
            <xs:element name="Department" type="myidbase:String64" minOccurs="0"/>
            <xs:element name="BaseDN" type="myidbase:String255" minOccurs="0"/>
            <xs:element name="Parent" type="myidbase:String80" minOccurs="0"/>
            <xs:element name="AgencyAddress" minOccurs="0" maxOccurs="1" type="AgencyAddressBlockType"/>
            <xs:element name="AdditionalAgencyFields" minOccurs="0" maxOccurs="1">
                <xs:complexType mixed="true">
                    <xs:sequence>
```

```
<xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Applicant" minOccurs="0" maxOccurs="unbounded" type="ApplicantBlockType"/>
</xs:sequence>
</xs:complexType>

<xs:complexType name="ApplicantBlockType">
<xs:sequence>
<xs:element name="Personal" minOccurs="0" type="PersonalBlockType"/>
<xs:element name="Authentication" minOccurs="0" maxOccurs="1" type="AuthenticationBlockType"/>
<xs:element name="Card" minOccurs="0" maxOccurs="1" type="CardBlockType"/>
<xs:element name="Account" minOccurs="0" type="AccountBlockType"/>
<xs:element name="Position" minOccurs="0" type="PositionBlockType"/>
<xs:element name="Sponsor" minOccurs="0" maxOccurs="1" type="SponsorBlockType"/>
<xs:element name="Biometry" minOccurs="0" type="BiometryBlockType"/>
<xs:element name="IdentityDocs" minOccurs="0" type="IdentityDocumentsBlockType"/>
<xs:element name="NACI" minOccurs="0" type="NACIStatusBlockType"/>
<xs:element name="Photo" minOccurs="0">
<xs:complexType>
<xs:group ref="EncodedData"/>
</xs:complexType>
</xs:element>
<xs:element name="System" minOccurs="0" type="SystemBlockType"/>
<xs:element name="AdditionalFields" minOccurs="0" maxOccurs="1">
<xs:complexType mixed="true">
<xs:sequence>
<xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Actions" minOccurs="0" maxOccurs="1">
</xs:element>
</xs:sequence>
</xs:complexType>

<xs:complexType name="SponsorBlockType">
<xs:sequence>
<xs:element name="SponsorName" type="myidbase:String80" minOccurs="0" maxOccurs="1"/>
<xs:element name="SponsorPosition" type="myidbase:String30" minOccurs="0" maxOccurs="1"/>
<xs:element name="SponsorAgency" type="myidbase:String80" minOccurs="0" maxOccurs="1"/>
<xs:element name="SponsorEmail" type="myidbase:String120" minOccurs="0" maxOccurs="1"/>
<xs:element name="SponsorPhoneNumber" type="myidbase:String30" minOccurs="0" maxOccurs="1"/>
```

```
</xs:sequence>
</xs:complexType>

<xs:complexType name="SystemBlockType">
<xs:sequence>
<xs:element name="GUID" type="myidbase:String50" minOccurs="0"/>
<xs:element name="CredNo" type="myidbase:String8" minOccurs="0"/>
<xs:element name="CS" type="xs:unsignedInt" minOccurs="0"/>
<xs:element name="POA" type="xs:unsignedInt" minOccurs="0"/>
<xs:element name="ICI" type="xs:unsignedInt" minOccurs="0"/>
<xs:element name="UserStatus" type="myidbase:String50" minOccurs="0"/>
<xs:element name="IssuanceNotifyURL" type="myidbase:String255" minOccurs="0"/>
<xs:element name="CancelNotifyURL" type="myidbase:String255" minOccurs="0"/>
<xs:element name="CMSIssuanceNotifyURL" type="myidbase:String255" minOccurs="0"/>
</xs:sequence>
</xs:complexType>

</xs:schema>
```

9.10 PivImportResponse

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="PIVImportResponse" targetNamespace="http://www.intercede.com/MyIDPIVSchema/PIVImportResponse"
 xmlns:mstns="http://www.intercede.com/MyIDPIVSchema/PIVImportResponse" attributeFormDefault="unqualified"
 elementFormDefault="qualified" xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:element name="PivImportResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element name="Agency" minOccurs="0" maxOccurs="unbounded">
                    <xs:complexType>
                        <xs:sequence>
                            <xs:element name="AgencyName" type="mstns:String80" minOccurs="1" maxOccurs="1"/>
                            <xs:element name="AgencyCode" type="mstns:String4" minOccurs="1" maxOccurs="1" />
                            <xs:element name="Result" type="mstns:ActionStatus" minOccurs="1" maxOccurs="1" />
                            <xs:element name="Applicant" minOccurs="0" maxOccurs="unbounded"
type="mstns:ApplicantType"/>
                        </xs:sequence>
                    </xs:complexType>
                </xs:element>
                <xs:element name="Applicant" minOccurs="0" maxOccurs="unbounded" type="mstns:ApplicantType"/>
                <xs:element name="error" minOccurs="0" maxOccurs="1">
                    <xs:complexType mixed="true">
                        <xs:sequence>
                            <xs:any minOccurs="0" maxOccurs="unbounded" processContents="skip"/>
                        </xs:sequence>
                    </xs:complexType>
                </xs:element>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
</xs:schema>
```

```
        </xs:sequence>
    </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:complexType name="ApplicantType">
    <xs:sequence>
        <xs:element name="FirstName" type="mstns:String64" minOccurs="1" maxOccurs="1"/>
        <xs:element name="LastName" type="mstns:String64" minOccurs="1" maxOccurs="1"/>
        <xs:element name="EmployeeID" type="mstns:Int50" minOccurs="1" maxOccurs="1"/>
        <xs:element name="CardRequest" type="xs:int" minOccurs="1" maxOccurs="1" />
    <xs:element name="CardRequestFailReason" type="mstns:String64" minOccurs="0" maxOccurs="1"/>
    <xs:element name="Result" type="mstns:ActionStatus" minOccurs="1" maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="String50">
    <xs:restriction base="xs:string">
        <xs:maxLength value="50" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String80">
    <xs:restriction base="xs:string">
        <xs:maxLength value="80" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String64">
    <xs:restriction base="xs:string">
        <xs:maxLength value="64" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="String4">
    <xs:restriction base="xs:string">
        <xs:maxLength value="4" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="Int50">
    <xs:restriction base="xs:string">
        <xs:maxLength value="50" />
        <xs:pattern value="[0-9]*" />
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ActionStatus">
    <xs:restriction base="xs:string">
```

```
<xs:enumeration value="Added"/>
<xs:enumeration value="Created"/>
<xs:enumeration value="Already Exists"/>
<xs:enumeration value="Failed"/>
<xs:enumeration value="Removed"/>
<xs:enumeration value="License Limit"/>
</xs:restriction>
</xs:simpleType>
</xs:schema>
```